

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | L G W8 5 2 2 1 S        |
| 光源       | LLD2000LCE1 ×1 531.0 lm |
| 管理番号     | K0190582 ( 0 ) DR 1     |
| BZ分類     | BZ10                    |

| 器具効率     |                 | 55 %            | 反射率             | 天井            | 80 % |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |  |   |    |
|----------|-----------------|-----------------|-----------------|---------------|------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|--|---|----|
|          |                 |                 |                 | 壁             | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |  |   |    |
|          |                 |                 |                 | 床             | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |  |   |    |
| 上方光束     |                 | 27 %            | 室指数             | 照明率 ( X0.01 ) |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  | Z | CM |
| 下方光束     |                 | 28 %            |                 |               |      |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |  |   |    |
| 保守率      |                 | 良<br>中<br>否     | 0.63            | 0.6           | 23   | 16 | 12 | 9  | 21   | 15 | 11 | 8  | 17   | 12 | 9  | 6  | 13   | 9  | 7  | 5  | 2   |  |   |    |
|          |                 |                 | 0.6             | 0.8           | 28   | 21 | 16 | 12 | 25   | 19 | 15 | 11 | 20   | 15 | 12 | 9  | 16   | 12 | 9  | 7  | 4   |  |   |    |
|          |                 |                 | 0.56            | 1.0           | 31   | 24 | 19 | 16 | 28   | 22 | 18 | 14 | 23   | 18 | 15 | 12 | 18   | 14 | 11 | 9  | 5   |  |   |    |
|          |                 |                 |                 | 1.25          | 34   | 28 | 23 | 19 | 31   | 25 | 21 | 17 | 25   | 21 | 17 | 14 | 20   | 17 | 14 | 11 | 6   |  |   |    |
| 下方投影面積   |                 | cm <sup>2</sup> | 1.5             | 36            | 30   | 26 | 22 | 33 | 28   | 23 | 20 | 27 | 23   | 19 | 17 | 21 | 18   | 16 | 13 | 8  |     |  |   |    |
| 等価発光面積   |                 |                 | cm <sup>2</sup> | 2.0           | 39   | 34 | 30 | 26 | 36   | 31 | 27 | 24 | 30   | 26 | 23 | 20 | 24   | 21 | 18 | 16 | 10  |  |   |    |
| 取付<br>高さ | 器具間隔最大限         |                 | 2.5             | 41            | 37   | 33 | 29 | 38 | 34   | 30 | 27 | 31 | 28   | 25 | 23 | 25 | 23   | 21 | 19 | 12 |     |  |   |    |
|          | 横方向 (A) 縦方向 (B) |                 | 3.0             | 43            | 39   | 35 | 32 | 39 | 36   | 32 | 29 | 33 | 30   | 27 | 25 | 27 | 24   | 22 | 20 | 13 |     |  |   |    |
| H m      | 0.00 H m        | 1.73 H m        | 4.0             | 45            | 41   | 38 | 35 | 41 | 38   | 35 | 33 | 35 | 32   | 30 | 28 | 28 | 26   | 24 | 23 | 15 |     |  |   |    |
|          |                 |                 | 5.0             | 46            | 43   | 40 | 38 | 43 | 40   | 37 | 35 | 36 | 34   | 32 | 30 | 29 | 28   | 26 | 25 | 17 |     |  |   |    |
|          |                 |                 | 7.0             | 48            | 46   | 43 | 41 | 44 | 42   | 40 | 38 | 37 | 36   | 34 | 33 | 31 | 29   | 28 | 27 | 19 |     |  |   |    |
|          |                 |                 | 10.0            | 49            | 47   | 46 | 44 | 46 | 44   | 42 | 41 | 39 | 37   | 36 | 35 | 32 | 31   | 30 | 29 | 20 |     |  |   |    |

