

| 屋内照明器具特性 |                         |
|----------|-------------------------|
| 品番 (品名)  | L G W8 5 2 2 1 Y        |
| 光源       | LLD4000LCE1 ×1 845.0 lm |
| 管理番号     | K0190581 ( 0 ) DR 1     |
| B Z 分類   | BZ10                    |

| 器具効率     |                     | 54 %            | 反射率    | 天井              | 80 %              |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|---------------------|-----------------|--------|-----------------|-------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |                     |                 |        | 壁               | 70                | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |                     |                 |        | 床               | 10 %              |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |                     |                 |        | 室指数             | 照明率 ( X0.01 ) ZCM |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |                     | 良<br>中<br>否     | 0.63   | 0.6             | 23                | 16 | 11 | 8  | 21   | 14 | 10 | 8  | 17   | 12 | 8  | 6  | 13   | 9  | 7  | 5  | 2   |
|          |                     |                 | 0.6    | 0.8             | 27                | 20 | 16 | 12 | 25   | 19 | 14 | 11 | 20   | 15 | 12 | 9  | 16   | 12 | 9  | 7  | 3   |
|          |                     |                 | 0.56   | 1.0             | 30                | 24 | 19 | 15 | 28   | 22 | 17 | 14 | 22   | 18 | 14 | 12 | 18   | 14 | 11 | 9  | 5   |
|          |                     |                 |        | 1.25            | 33                | 27 | 22 | 19 | 30   | 25 | 21 | 17 | 25   | 20 | 17 | 14 | 20   | 16 | 14 | 11 | 6   |
| 下方投影面積   |                     | cm <sup>2</sup> |        | 1.5             | 36                | 30 | 25 | 21 | 32   | 27 | 23 | 20 | 27   | 22 | 19 | 16 | 21   | 18 | 15 | 13 | 8   |
|          |                     |                 | 等価発光面積 | cm <sup>2</sup> | 2.0               | 39 | 33 | 29 | 26   | 35 | 31 | 27 | 24   | 29 | 25 | 22 | 20   | 23 | 20 | 18 | 16  |
| 取付<br>高さ | 器具間隔最大限             |                 |        | 2.5             | 41                | 36 | 32 | 29 | 37   | 33 | 30 | 27 | 31   | 28 | 25 | 22 | 25   | 22 | 20 | 18 | 12  |
|          | 横方向 ( A ) 縦方向 ( B ) |                 |        | 3.0             | 42                | 38 | 34 | 31 | 39   | 35 | 32 | 29 | 32   | 29 | 27 | 24 | 26   | 24 | 22 | 20 | 13  |
| H m      | 0.00 H m 1.72 H m   |                 |        | 4.0             | 44                | 41 | 38 | 35 | 41   | 38 | 35 | 32 | 34   | 32 | 29 | 27 | 28   | 26 | 24 | 22 | 15  |
|          |                     |                 |        | 5.0             | 45                | 42 | 40 | 37 | 42   | 39 | 37 | 35 | 35   | 33 | 31 | 29 | 29   | 27 | 26 | 24 | 16  |
|          |                     |                 |        | 7.0             | 47                | 45 | 42 | 40 | 43   | 41 | 39 | 37 | 37   | 35 | 33 | 32 | 30   | 29 | 28 | 26 | 18  |
|          |                     |                 |        | 10.0            | 48                | 46 | 45 | 43 | 45   | 43 | 42 | 40 | 38   | 37 | 35 | 34 | 32   | 30 | 29 | 29 | 20  |

