

屋内照明器具特性	
品番 (品名)	L G W8 5 2 2 1 Y
光源	L L D 2 0 2 0 L C T 1 × 1 4 6 0 . 0 l m
管理番号	K 0 1 9 0 5 9 3 (0) D R 1
B Z 分類	B Z 1 0

器具効率		60 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		30 %	室指数	照明率 (X0.01)																			Z	CM
下方光束		30 %																						
保守率		良 中 否	0.63	0.6	26	18	13	9	23	16	12	8	19	13	9	7	15	10	7	5	2			
			0.6	0.8	31	23	17	14	28	21	16	12	22	17	13	10	18	13	10	8	4			
			0.56	1.0	34	27	21	17	31	24	19	16	25	20	16	13	20	16	13	10	5			
				1.25	37	30	25	21	34	28	23	19	28	23	19	16	22	18	15	13	7			
下方投影面積		cm ²		1.5	40	33	28	24	36	30	26	22	30	25	21	18	24	20	17	15	8			
等価発光面積			cm ²	2.0	43	38	33	29	40	34	30	26	33	28	25	22	26	23	20	18	11			
取付 高さ	器具間隔最大限		2.5	46	40	36	32	42	37	33	30	35	31	28	25	28	25	22	20	13				
	横方向 (A)		縦方向 (B)		3.0	47	43	39	35	43	39	36	32	36	33	30	27	29	27	24	22	14		
H m	0.00 H m	1.66 H m	4.0	50	46	42	39	46	42	39	36	38	35	33	30	31	29	27	25	17				
			5.0	51	48	45	42	47	44	41	39	39	37	35	33	32	30	29	27	18				
			7.0	53	50	48	45	49	46	44	42	41	39	37	36	34	32	31	30	20				
			10.0	54	52	50	48	50	48	47	45	43	41	40	38	35	34	33	32	22				

