

屋内照明器具特性	
品番 (品名)	L G W C 8 5 2 2 1 B
光源	L D A 4 L - H - E 1 7 / S / 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 9 0 5 9 5 (0) D R 1
B Z 分類	B Z 1 0 / 0 . 9 / B Z 9 / 3 . 5 / B Z 1 0 / 4 . 5 / B Z 9

器具効率		4 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		2 2 %	室指数	照明率 (X 0 . 0 1) Z C M																	
下方光束		2 2 %																			
保守率		良 中 否	0 . 6 3	0 . 6	1 9	1 3	1 0	7	1 7	1 2	9	6	1 4	1 0	7	5	1 1	8	6	4	2
			0 . 6	0 . 8	2 2	1 7	1 3	1 0	2 0	1 5	1 2	9	1 6	1 3	1 0	8	1 3	1 0	8	6	3
			0 . 5 6	1 . 0	2 5	2 0	1 6	1 3	2 3	1 8	1 4	1 2	1 8	1 5	1 2	1 0	1 4	1 2	9	8	4
				1 . 2 5	2 7	2 2	1 8	1 6	2 5	2 0	1 7	1 4	2 0	1 7	1 4	1 2	1 6	1 3	1 1	9	5
下方投影面積		c m ²	1 . 5	2 9	2 4	2 1	1 8	2 6	2 2	1 9	1 6	2 2	1 8	1 6	1 4	1 7	1 5	1 3	1 1	6	
等価発光面積			c m ²	2 . 0	3 2	2 7	2 4	2 1	2 9	2 5	2 2	2 0	2 4	2 1	1 8	1 6	1 9	1 7	1 5	1 3	8
取付 高さ	器具間隔最大限		2 . 5	3 3	2 9	2 6	2 4	3 0	2 7	2 4	2 2	2 5	2 3	2 0	1 8	2 0	1 8	1 7	1 5	1 0	
	横方向 (A) 縦方向 (B)		3 . 0	3 4	3 1	2 8	2 6	3 2	2 9	2 6	2 4	2 6	2 4	2 2	2 0	2 1	1 9	1 8	1 6	1 1	
H m	0 . 0 0 H m	1 . 7 2 H m	4 . 0	3 6	3 3	3 1	2 9	3 3	3 1	2 8	2 6	2 8	2 6	2 4	2 2	2 2	2 1	2 0	1 8	1 2	
			5 . 0	3 7	3 5	3 2	3 0	3 4	3 2	3 0	2 8	2 9	2 7	2 5	2 4	2 3	2 2	2 1	2 0	1 3	
			7 . 0	3 8	3 6	3 5	3 3	3 5	3 4	3 2	3 1	3 0	2 8	2 7	2 6	2 4	2 3	2 2	2 2	1 5	
			1 0 . 0	3 9	3 8	3 6	3 5	3 6	3 5	3 4	3 3	3 1	3 0	2 9	2 8	2 5	2 5	2 4	2 3	1 6	

