

屋内照明器具特性	
品番 (品名)	XLGE8021
光源	LLD2000NCE1 ×1 531.0 lm
管理番号	K0190582 (0) DR 1
BZ分類	BZ10

器具効率		55 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %					10 %					10 %					10 %					0 %
						室指数	照明率 (X0.01)																			
保守率		良 中 否	0.63	0.6	0.6	23	16	12	9	21	15	11	8	17	12	9	6	13	9	7	5	2				
			0.6	0.8	28	21	16	12	25	19	15	11	20	15	12	9	16	12	9	7	4					
			0.56	1.0	31	24	19	16	28	22	18	14	23	18	15	12	18	14	11	9	5					
			1.25	34	28	23	19	31	25	21	17	25	21	17	14	20	17	14	11	6						
下方投影面積		cm ²	1.5	36	30	26	22	33	28	23	20	27	23	19	17	21	18	16	13	8						
等価発光面積			2.0	39	34	30	26	36	31	27	24	30	26	23	20	24	21	18	16	10						
取付 高さ	器具間隔最大限			2.5	41	37	33	29	38	34	30	27	31	28	25	23	25	23	21	19	12					
	横方向 (A)		縦方向 (B)	3.0	43	39	35	32	39	36	32	29	33	30	27	25	27	24	22	20	13					
H m	0.00 H m		1.73 H m	4.0	45	41	38	35	41	38	35	33	35	32	30	28	28	26	24	23	15					
				5.0	46	43	40	38	43	40	37	35	36	34	32	30	29	28	26	25	17					
				7.0	48	46	43	41	44	42	40	38	37	36	34	33	31	29	28	27	19					
				10.0	49	47	46	44	46	44	42	41	39	37	36	35	32	31	30	29	20					

