

屋内照明器具特性	
品番 (品名)	XLGE8032
光源	LLD4000LCE1 ×1 845.0 lm
管理番号	K0190581 (0) DR 1
BZ分類	BZ10

器具効率		54 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																
保守率		良 中 否	0.63	0.6	23	16	11	8	21	14	10	8	17	12	8	6	13	9	7	5	2
			0.6	0.8	27	20	16	12	25	19	14	11	20	15	12	9	16	12	9	7	3
			0.56	1.0	30	24	19	15	28	22	17	14	22	18	14	12	18	14	11	9	5
			1.25	33	27	22	19	30	25	21	17	25	20	17	14	20	16	14	11	6	
下方投影面積		cm ²	1.5	36	30	25	21	32	27	23	20	27	22	19	16	21	18	15	13	8	
			2.0	39	33	29	26	35	31	27	24	29	25	22	20	23	20	18	16	10	
等価発光面積		cm ²	2.5	41	36	32	29	37	33	30	27	31	28	25	22	25	22	20	18	12	
			3.0	42	38	34	31	39	35	32	29	32	29	27	24	26	24	22	20	13	
H m	0.00 H m	1.72 H m	4.0	44	41	38	35	41	38	35	32	34	32	29	27	28	26	24	22	15	
			5.0	45	42	40	37	42	39	37	35	35	33	31	29	29	27	26	24	16	
			7.0	47	45	42	40	43	41	39	37	37	35	33	32	30	29	28	26	18	
			10.0	48	46	45	43	45	43	42	40	38	37	35	34	32	30	29	29	20	

