

屋内照明器具特性	
品番 (品名)	LGB15458K
光源	LDA4L-H-E17/S/4 ×1 440.0lm
管理番号	K0164281(1)DB1
BZ分類	BZ4/0.7/BZ3/1.8/BZ4

器具効率		57 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	34	27	23	20	33	27	23	20	31	26	22	20	29	25	22	19	18
			0.63	0.8	39	34	30	27	38	33	29	26	36	32	28	26	34	30	28	25	24
			0.56	1.0	43	38	34	31	42	37	33	31	40	36	32	30	38	34	31	29	28
				1.25	46	41	38	35	45	41	37	35	43	39	36	34	41	37	35	33	31
下方投影面積		cm ²	1.5	48	44	41	38	47	43	40	37	45	41	39	37	42	40	37	36	34	
			2.0	51	48	45	42	50	47	44	42	47	45	42	40	45	43	41	39	37	
等価発光面積		cm ²	2.5	53	50	47	45	52	49	46	44	49	47	45	43	47	45	43	42	39	
			3.0	54	51	49	47	53	50	48	46	50	48	46	45	48	46	45	43	41	
H _m	1.37 H _m	1.40 H _m	4.0	56	53	51	50	54	52	51	49	52	50	49	47	49	48	47	46	43	
			5.0	56	55	53	52	55	53	52	51	53	51	50	49	50	49	48	47	44	
			7.0	57	56	55	54	56	55	54	53	54	53	52	51	51	51	50	49	46	
			10.0	58	57	56	55	57	56	55	54	55	54	53	52	52	52	51	50	47	

