

屋内照明器具特性	
品番 (品名)	L G B 1 6 4 5 3 K
光源	L D A 4 W W - H - E 1 7 / S / 4 × 1 4 4 0 . 0 1 m
管理番号	K 0 1 7 0 9 5 7 (0) D R 1
B Z 分類	B Z 6 / 0 . 7 / B Z 5 / 1 . 1 / B Z 6

器具効率		9 8 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	5 0	3 9	3 1	2 6	4 8	3 7	3 0	2 5	4 3	3 4	2 8	2 3	3 9	3 1	2 6	2 2	1 8
			0 . 6 3	0 . 8	5 9	4 8	4 0	3 4	5 6	4 6	3 9	3 3	5 0	4 2	3 6	3 1	4 5	3 8	3 3	2 9	2 5
			0 . 5 6	1 . 0	6 5	5 4	4 6	4 1	6 2	5 2	4 5	3 9	5 5	4 7	4 1	3 7	5 0	4 3	3 8	3 4	2 9
				1 . 2 5	7 1	6 0	5 3	4 7	6 7	5 8	5 1	4 5	6 0	5 3	4 7	4 2	5 4	4 8	4 3	3 9	3 3
下方投影面積		c m ²	1 . 5	7 4	6 5	5 8	5 2	7 1	6 2	5 5	5 0	6 3	5 7	5 1	4 7	5 7	5 1	4 7	4 3	3 7	
			2 . 0	8 0	7 1	6 5	5 9	7 6	6 8	6 2	5 7	6 8	6 2	5 7	5 3	6 1	5 7	5 3	4 9	4 2	
等価発光面積		c m ²	2 . 5	8 3	7 6	7 0	6 5	7 9	7 2	6 7	6 2	7 1	6 6	6 2	5 8	6 4	6 0	5 6	5 3	4 6	
			3 . 0	8 5	7 9	7 3	6 9	8 1	7 6	7 1	6 6	7 4	6 9	6 5	6 1	6 6	6 3	5 9	5 6	4 8	
H m	1 . 3 4 H m	1 . 3 4 H m	4 . 0	8 8	8 3	7 9	7 4	8 4	8 0	7 5	7 2	7 7	7 3	6 9	6 6	6 9	6 6	6 3	6 1	5 2	
			5 . 0	9 0	8 6	8 2	7 8	8 6	8 2	7 9	7 5	7 9	7 5	7 2	6 9	7 1	6 9	6 6	6 4	5 5	
			7 . 0	9 3	8 9	8 6	8 3	8 9	8 6	8 3	8 0	8 1	7 8	7 6	7 4	7 4	7 2	7 0	6 8	5 9	
			1 0 . 0	9 5	9 2	9 0	8 7	9 1	8 8	8 6	8 4	8 3	8 1	7 9	7 7	7 6	7 4	7 3	7 1	6 2	

