

屋内照明器具特性	
品番 (品名)	L G B 1 5 4 6 6 K
光源	LDA4 L - H - E17 / S / 4 ×1 440.0 lm
管理番号	K0170955 (0) DR 1
B Z 分類	BZ5 / 0.9 / BZ4

器具効率		60 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	34	27	22	19	33	26	22	18	32	26	21	18	30	25	21	18	17
			0.63	0.8	40	33	29	25	39	33	29	25	38	32	28	25	36	31	28	25	24
			0.56	1.0	45	38	34	30	44	38	34	30	42	37	33	30	40	36	33	30	29
				1.25	48	43	39	36	48	42	38	35	46	41	38	35	44	40	37	35	34
下方投影面積 等価発光面積		c m ² c m ²		1.5	51	46	42	39	50	46	42	39	48	44	41	39	47	43	41	38	37
				2.0	55	50	47	44	54	50	47	44	52	49	46	44	50	48	45	43	42
				2.5	57	53	50	48	56	53	50	48	54	51	49	47	52	50	48	47	45
取付 高さ	器具間隔最大限			3.0	58	55	53	50	57	54	52	50	55	53	51	49	54	52	50	49	47
	横方向 (A)	縦方向 (B)		4.0	60	58	55	54	59	57	55	53	57	56	54	53	56	54	53	52	50
H m	1.34 H m	1.34 H m		5.0	61	59	57	56	60	58	57	55	58	57	56	54	57	56	55	54	52
				7.0	62	61	59	58	61	60	59	58	60	59	58	57	58	57	57	56	54
				10.0	63	62	61	60	62	61	60	60	61	60	59	58	59	59	58	57	56

