

屋内照明器具特性	
品番 (品名)	L G B 1 6 0 0 3 F
光源	LDA4 L - H - E17 / S / 4 ×1 440.0 lm
管理番号	K0122381 (0) DB 1
B Z 分類	BZ5

器具効率		91 %	反射率	天井	80 %				70 %				50 %				30 %				0 %		
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %		
				床	10 %				10 %				10 %				10 %				0 %		
				室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.67	0.6	50	39	32	27	49	38	31	27	46	37	31	26	43	35	30	26	24		
			0.63	0.8	59	49	42	36	58	48	41	36	54	46	40	35	52	44	39	35	32		
			0.56	1.0	65	56	49	43	64	55	48	43	60	53	47	42	57	51	45	41	39		
				1.25	71	62	56	50	69	61	55	50	66	59	53	49	63	57	52	48	45		
下方投影面積 等価発光面積		cm ² cm ²		1.5	75	67	61	56	73	66	60	55	70	63	58	54	66	61	57	53	50		
				2.0	80	74	68	64	78	72	67	63	75	70	65	62	71	67	63	60	57		
				2.5	83	78	73	69	82	76	72	68	78	74	70	67	75	71	68	65	62		
				3.0	86	81	77	73	84	79	76	72	80	77	73	70	77	74	71	69	65		
取付 高さ	器具間隔最大限			4.0	89	85	81	78	87	83	80	77	83	80	78	75	80	77	75	73	70		
	横方向 (A)		縦方向 (B)			5.0	90	87	84	82	88	86	83	80	85	83	80	78	82	80	78	76	
						7.0	92	90	88	86	90	88	86	84	87	85	84	82	84	82	81	80	76
						10.0	94	92	90	89	92	90	89	87	89	87	86	85	85	84	83	82	78

