

屋内照明器具特性	
品番 (品名)	L G B 1 6 0 5 8 F
光源	LDA4 L - H - E17 / S / 4 ×1 440.0 lm
管理番号	K0127994 (0) DB 1
B Z 分類	BZ5 / 1.1 / BZ4 / 6.0 / BZ5

器具効率		93 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		10 % 83 %	室指数	照明率 (X0.01) Z C M																		
保守率		良 中 否	0.67	0.6	51	40	33	28	50	39	32	27	46	37	31	27	44	36	30	26	24	
			0.63	0.8	61	50	43	38	59	49	43	38	55	47	41	37	52	45	40	36	33	
			0.56	1.0	67	58	51	46	65	56	50	45	61	54	48	44	58	51	47	43	40	
				1.25	73	64	58	53	71	63	57	52	67	60	55	51	63	57	53	49	46	
下方投影面積		cm ²	1.5	77	69	63	58	75	67	62	57	70	64	60	56	67	62	58	54	51		
等価発光面積		cm ²	2.0	82	75	70	66	80	74	69	65	75	70	66	63	71	67	64	61	57		
取付 高さ	器具間隔最大限		2.5	85	80	75	71	83	78	73	70	78	74	71	68	74	71	68	65	61		
	横方向 (A) 縦方向 (B)		3.0	87	82	78	75	85	81	77	73	81	77	74	71	77	74	71	69	64		
H m	1.38 H m	1.38 H m	4.0	90	86	83	80	88	84	81	78	83	80	78	75	79	77	75	73	68		
			5.0	92	88	85	83	89	86	84	81	85	83	80	78	81	79	77	76	71		
			7.0	93	91	89	87	91	89	87	85	87	85	83	82	83	82	80	79	74		
			10.0	95	93	91	90	93	91	90	88	89	87	86	85	85	83	82	81	76		

