

| 屋内照明器具特性 |                                       |
|----------|---------------------------------------|
| 品番 (品名)  | L G B 1 6 7 1 0 K                     |
| 光源       | LDA4 L - H - E17 / S / 4 ×1 440.0 l m |
| 管理番号     | K0123182 ( 0 ) DB 1                   |
| BZ分類     | BZ5 / 1.1 / BZ6                       |

| 器具効率             | 77 %<br><br>上方光束<br>28 %<br>下方光束<br>49 % | 天井   | 80 %                |    |    |    | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|------------------|------------------------------------------|------|---------------------|----|----|----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|                  |                                          | 反射率  | 70                  | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|                  |                                          | 室指数  | 照明率 ( X0.01 ) Z C M |    |    |    |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率              | 良 0.67                                   | 0.6  | 41                  | 32 | 26 | 22 | 38   | 30 | 25 | 21 | 34   | 27 | 23 | 20 | 30   | 24 | 21 | 18 | 15  |
|                  | 中 0.63                                   | 0.8  | 46                  | 38 | 32 | 28 | 44   | 36 | 31 | 27 | 38   | 32 | 28 | 24 | 33   | 29 | 25 | 22 | 18  |
|                  | 否 0.56                                   | 1.0  | 51                  | 42 | 36 | 32 | 47   | 40 | 35 | 31 | 42   | 36 | 31 | 28 | 36   | 32 | 28 | 25 | 20  |
|                  |                                          | 1.25 | 54                  | 47 | 41 | 36 | 51   | 44 | 39 | 35 | 45   | 39 | 35 | 31 | 39   | 35 | 31 | 28 | 23  |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup>                          | 1.5  | 57                  | 50 | 44 | 40 | 54   | 47 | 42 | 38 | 47   | 42 | 38 | 34 | 41   | 37 | 33 | 31 | 25  |
|                  | cm <sup>2</sup>                          | 2.0  | 61                  | 55 | 50 | 45 | 57   | 52 | 47 | 43 | 50   | 46 | 42 | 39 | 44   | 40 | 37 | 35 | 28  |
|                  |                                          | 2.5  | 64                  | 58 | 53 | 49 | 60   | 55 | 50 | 47 | 52   | 49 | 45 | 42 | 46   | 43 | 40 | 37 | 30  |
| 取付高さ             | 器具間隔最大限<br>横方向 (A) 縦方向 (B)               | 3.0  | 65                  | 60 | 56 | 52 | 62   | 57 | 53 | 50 | 54   | 51 | 47 | 45 | 47   | 44 | 42 | 40 | 32  |
| H m              | 0.76 H m 0.76 H m                        | 4.0  | 68                  | 64 | 60 | 57 | 64   | 60 | 57 | 54 | 56   | 53 | 51 | 48 | 49   | 47 | 45 | 43 | 34  |
|                  |                                          | 5.0  | 69                  | 66 | 63 | 60 | 66   | 62 | 59 | 57 | 58   | 55 | 53 | 51 | 51   | 49 | 47 | 45 | 36  |
|                  |                                          | 7.0  | 71                  | 69 | 66 | 63 | 67   | 65 | 62 | 60 | 60   | 58 | 56 | 54 | 52   | 51 | 49 | 48 | 39  |
|                  |                                          | 10.0 | 73                  | 71 | 69 | 67 | 69   | 67 | 65 | 63 | 61   | 60 | 58 | 57 | 54   | 53 | 52 | 50 | 41  |

