

屋内照明器具特性	
品番 (品名)	LGB15021AF
光源	LDA4L-H-E17/S/4 ×1 440.0 lm
管理番号	K0170216 (0) DR 1
BZ分類	BZ5/2.8/BZ4

器具効率		96 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.67	0.6	54	42	34	29	52	41	34	29	50	40	33	29	48	39	33	28	27				
			0.63	0.8	64	52	45	39	62	52	44	39	59	50	44	39	57	49	43	39	36				
			0.56	1.0	70	60	52	47	69	59	52	46	66	57	51	46	63	56	50	46	44				
				1.25	76	67	60	54	75	66	59	54	72	64	58	54	69	62	57	53	51				
下方投影面積 等価発光面積		cm ²		1.5	80	72	65	60	79	71	65	60	76	69	64	59	73	67	63	59	56				
			cm ²	2.0	86	79	73	68	84	78	72	68	81	76	71	67	79	74	70	66	64				
取付 高さ	器具間隔最大限			2.5	89	83	78	74	88	82	78	74	85	80	76	73	82	78	75	72	69				
	横方向 (A) 縦方向 (B)			3.0	92	87	82	78	90	85	81	78	87	83	80	77	85	81	78	76	73				
H m	1.33 H m	1.33 H m		4.0	95	91	87	84	93	90	86	83	91	87	85	82	88	85	83	81	78				
				5.0	97	93	90	87	95	92	89	87	93	90	88	85	90	88	86	84	81				
			7.0	99	96	94	92	97	95	93	91	95	93	91	89	92	91	89	88	85					
			10.0	100	98	97	95	99	97	96	94	96	95	94	93	94	93	92	91	88					

