

屋内照明器具特性	
品番 (品名)	LGB87024F
光源	LDA4L-H-E17/S/4 ×1 440.0 lm
管理番号	K0123323 (0) DB1
BZ分類	BZ4/1.4/BZ5

器具効率		79 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.67	0.6	45	36	31	27	43	35	30	26	39	32	28	25	35	30	26	24	21
			0.63	0.8	51	43	37	33	49	41	36	32	44	38	34	30	40	35	31	29	25
			0.56	1.0	56	48	42	38	53	46	41	37	48	42	38	34	43	38	35	32	28
				1.25	59	52	47	42	57	50	45	41	51	46	42	38	46	42	39	36	31
下方投影面積		cm ²	1.5	62	56	50	46	59	53	48	45	53	49	45	42	48	44	41	39	33	
			2.0	66	60	56	52	63	58	53	50	57	53	49	46	51	48	45	43	37	
取付 高さ	器具間隔最大限		2.5	69	64	59	56	65	61	57	54	59	55	52	50	53	50	48	46	39	
	横方向 (A)		縦方向 (B)	3.0	70	66	62	59	67	63	60	56	61	58	55	52	55	52	50	48	41
H _m	1.07 H _m		1.06 H _m	4.0	73	69	66	63	69	66	63	60	63	60	58	56	57	55	53	51	44
				5.0	74	71	68	66	71	68	65	63	64	62	60	58	58	56	55	53	46
				7.0	76	73	71	69	72	70	68	66	66	64	63	61	60	58	57	56	48
				10.0	77	75	74	72	74	72	71	69	67	66	65	64	61	60	59	58	50

