

屋内照明器具特性	
品番 (品名)	LGB87062Z
光源	LDA4L-H-E17/S/4 ×1 440.0 lm
管理番号	K0187162 (0) DR 1
BZ分類	BZ6

器具効率		95 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
上方光束		36 %	室指数	照明率 (X0.01)																				Z	CM
下方光束		59 %																							
保守率		良 中 否	0.67	0.6	47	36	29	24	44	34	27	22	38	30	24	20	33	26	22	18	14				
			0.63	0.8	55	44	37	31	52	42	35	30	45	37	31	27	39	32	28	24	19				
			0.56	1.0	61	50	43	37	57	48	41	36	49	42	36	32	43	37	32	29	23				
				1.25	66	56	49	43	62	53	47	41	54	47	42	37	46	41	37	33	26				
下方投影面積		cm ²	1.5	70	61	54	48	65	57	51	46	57	50	45	41	49	44	40	37	29					
等価発光面積		cm ²	2.0	75	67	61	55	70	63	57	53	61	56	51	47	53	49	45	42	33					
取付 高さ	器具間隔最大限		2.5	78	71	66	61	73	67	62	58	64	59	55	52	56	52	49	46	36					
	横方向 (A)	縦方向 (B)	3.0	80	74	69	65	76	70	65	61	66	62	58	55	57	54	51	49	39					
H _m	1.23 H _m	1.27 H _m	4.0	83	78	74	70	78	74	70	66	69	66	62	59	60	57	55	53	42					
			5.0	85	81	77	74	80	77	73	70	71	68	65	63	62	59	57	55	44					
			7.0	88	84	81	79	83	80	77	74	73	71	69	66	64	62	60	59	47					
			10.0	90	87	85	82	85	82	80	78	75	73	71	70	66	64	63	62	50					

