

屋内照明器具特性	
品番 (品名)	L G B 8 7 0 8 2 Z
光源	LDA4 L - H - E17 / S / 4 ×1 440.0 l m
管理番号	K0185908 (0) DB 1
B Z 分類	BZ5 / 1.8 / BZ6

器具効率		92 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
				室指数	照明率 (X0.01) Z C M																	
保守率		良 中 否	0.67	0.6	47	37	30	25	45	35	29	24	40	32	26	22	35	29	24	21	17	
			0.63	0.8	55	45	38	32	52	43	36	31	46	39	33	29	41	35	30	27	22	
			0.56	1.0	61	51	44	38	57	48	42	37	51	44	38	34	45	39	35	31	26	
				1.25	66	56	50	44	62	54	47	42	55	48	43	39	49	43	39	36	29	
下方投影面積		c m ²		1.5	69	61	54	49	65	58	52	47	58	52	47	43	51	46	42	39	32	
等価発光面積			c m ²	2.0	74	67	61	56	70	63	58	53	62	57	53	49	55	51	47	44	37	
取付高さ	器具間隔最大限			2.5	77	71	65	61	73	67	62	58	65	60	56	53	58	54	51	48	40	
	横方向 (A)			縦方向 (B)	3.0	79	74	69	64	75	70	66	62	67	63	59	56	60	56	53	51	42
H m	1.20 H m	1.15 H m		4.0	82	78	73	70	78	74	70	67	70	66	63	61	62	60	57	55	46	
			5.0	84	80	76	73	80	76	73	70	72	69	66	64	64	62	59	58	48		
			7.0	86	83	80	78	82	79	77	74	74	72	69	67	66	64	63	61	51		
			10.0	88	86	84	81	84	82	80	78	76	74	72	71	68	66	65	64	54		

