

屋内照明器具特性	
品番 (品名)	L G B 8 7 0 8 3 Z
光源	LDA4 L - H - E17 / S / 4 ×1 440.0 l m
管理番号	K0185908 (0) DB 1
BZ分類	BZ5 / 1.8 / BZ6

器具効率		9 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 7	0 . 6	4 7	3 7	3 0	2 5	4 5	3 5	2 9	2 4	4 0	3 2	2 6	2 2	3 5	2 9	2 4	2 1	1 7
			0 . 6 3	0 . 8	5 5	4 5	3 8	3 2	5 2	4 3	3 6	3 1	4 6	3 9	3 3	2 9	4 1	3 5	3 0	2 7	2 2
			0 . 5 6	1 . 0	6 1	5 1	4 4	3 8	5 7	4 8	4 2	3 7	5 1	4 4	3 8	3 4	4 5	3 9	3 5	3 1	2 6
				1 . 2 5	6 6	5 6	5 0	4 4	6 2	5 4	4 7	4 2	5 5	4 8	4 3	3 9	4 9	4 3	3 9	3 6	2 9
下方投影面積		c m ²		1 . 5	6 9	6 1	5 4	4 9	6 5	5 8	5 2	4 7	5 8	5 2	4 7	4 3	5 1	4 6	4 2	3 9	3 2
			等価発光面積	c m ²	2 . 0	7 4	6 7	6 1	5 6	7 0	6 3	5 8	5 3	6 2	5 7	5 3	4 9	5 5	5 1	4 7	4 4
取付 高さ	器具間隔最大限			2 . 5	7 7	7 1	6 5	6 1	7 3	6 7	6 2	5 8	6 5	6 0	5 6	5 3	5 8	5 4	5 1	4 8	4 0
	横方向 (A) 縦方向 (B)			3 . 0	7 9	7 4	6 9	6 4	7 5	7 0	6 6	6 2	6 7	6 3	5 9	5 6	6 0	5 6	5 3	5 1	4 2
H m	1 . 2 0 H m	1 . 1 5 H m		4 . 0	8 2	7 8	7 3	7 0	7 8	7 4	7 0	6 7	7 0	6 6	6 3	6 1	6 2	6 0	5 7	5 5	4 6
				5 . 0	8 4	8 0	7 6	7 3	8 0	7 6	7 3	7 0	7 2	6 9	6 6	6 4	6 4	6 2	5 9	5 8	4 8
				7 . 0	8 6	8 3	8 0	7 8	8 2	7 9	7 7	7 4	7 4	7 2	6 9	6 7	6 6	6 4	6 3	6 1	5 1
				1 0 . 0	8 8	8 6	8 4	8 1	8 4	8 2	8 0	7 8	7 6	7 4	7 2	7 1	6 8	6 6	6 5	6 4	5 4

