

屋内照明器具特性	
品番 (品名)	LGB87001F
光源	LDA4L-H-E17/S/4 ×1 440.0 lm
管理番号	K0122398 (1) DB1
BZ分類	BZ4/0.7/BZ3/0.9/BZ4

器具効率		34 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		4 % 30 %	室指数	照明率 (X0.01) ZCM																	
保守率		良 中 否	0.63	0.6	20	16	14	12	19	16	14	12	18	15	13	12	17	14	13	11	11
			0.6	0.8	23	20	17	15	22	19	17	15	21	18	16	15	20	17	16	14	13
			0.56	1.0	25	22	20	18	24	21	19	18	23	20	19	17	22	19	18	17	15
				1.25	27	24	22	20	26	23	21	20	25	22	21	19	23	21	20	19	17
下方投影面積		cm ²	1.5	28	26	24	22	27	25	23	22	26	24	22	21	24	23	21	20	19	
等価発光面積		cm ²	2.0	30	28	26	24	29	27	25	24	27	26	24	23	26	25	23	22	21	
取付 高さ	器具間隔最大限		2.5	31	29	28	26	30	28	27	26	28	27	26	25	27	26	25	24	22	
	横方向 (A) 縦方向 (B)		3.0	32	30	29	27	31	29	28	27	29	28	27	26	28	27	26	25	23	
H m	0.74 H m	1.24 H m	4.0	33	31	30	29	32	31	30	29	30	29	28	28	29	28	27	26	25	
			5.0	33	32	31	30	32	31	31	30	31	30	29	29	29	28	28	27	25	
			7.0	34	33	32	32	33	32	32	31	31	31	30	30	30	29	29	28	26	
			10.0	34	34	33	33	33	33	32	32	32	31	31	31	30	30	30	29	27	

