

屋内照明器具特性	
品番 (品名)	L G B 8 1 6 1 4 K
光源	LDA4 L - H - E17 / S / 4 ×1 440.0 lm
管理番号	K0170954 (0) DR 1
B Z 分類	BZ5 / 1.8 / BZ4

器具効率		79 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	44	34	28	23	43	34	27	23	41	33	27	23	39	32	27	23	21
			0.63	0.8	52	43	37	32	51	42	36	32	49	41	36	32	47	40	35	32	30
			0.56	1.0	58	49	43	39	57	49	43	38	54	47	42	38	52	46	42	38	36
				1.25	63	55	50	45	62	55	49	45	59	53	48	45	57	52	48	44	42
下方投影面積 等価発光面積		cm ² cm ²		1.5	66	59	54	50	65	59	54	50	63	57	53	49	60	56	52	49	47
				2.0	71	65	61	57	70	64	60	57	67	63	59	56	65	61	58	55	53
				2.5	74	69	65	62	73	68	64	61	70	66	63	60	68	65	62	60	58
				3.0	76	72	68	65	75	71	67	64	72	69	66	64	70	67	65	63	61
H _m	1.39 H _m	1.39 H _m		4.0	78	75	72	69	77	74	71	69	75	72	70	68	73	71	69	67	
				5.0	80	77	75	72	78	76	74	72	76	74	72	71	74	73	71	69	
				7.0	81	79	77	76	80	78	77	75	78	77	75	74	76	75	74	73	
				10.0	83	81	80	79	82	80	79	78	80	78	77	76	78	77	76	75	

