

屋内照明器具特性	
品番 (品名)	L G W8 5 0 1 5 S F
光源	L D A 4 L - H - E 1 7 / S / 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 2 6 0 5 6 (1) D B 1
B Z 分類	B Z 8 / 0 . 7 / B Z 7

器具効率		7 6 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束		2 8 %	室指数	照明率 (X 0 . 0 1)																	Z C M
下方光束		4 8 %																			
保守率		良	0 . 6 3	0 . 6	3 5	2 6	1 9	1 5	3 3	2 4	1 8	1 4	2 8	2 1	1 6	1 3	2 4	1 8	1 4	1 1	8
		中	0 . 6	0 . 8	4 2	3 3	2 6	2 1	3 9	3 0	2 5	2 0	3 4	2 7	2 2	1 8	2 9	2 3	1 9	1 6	1 2
		否	0 . 5 6	1 . 0	4 7	3 8	3 1	2 6	4 3	3 5	2 9	2 5	3 7	3 1	2 6	2 2	3 2	2 7	2 3	1 9	1 4
				1 . 2 5	5 1	4 2	3 6	3 1	4 7	4 0	3 4	2 9	4 1	3 5	3 0	2 6	3 5	3 0	2 6	2 3	1 7
下方投影面積		c m ²		1 . 5	5 4	4 6	4 0	3 5	5 0	4 3	3 8	3 3	4 4	3 8	3 3	3 0	3 7	3 3	2 9	2 6	2 0
等価発光面積		c m ²		2 . 0	5 8	5 2	4 6	4 1	5 5	4 8	4 3	3 9	4 7	4 2	3 8	3 5	4 1	3 7	3 4	3 1	2 4
取付 高さ	器具間隔最大限			2 . 5	6 1	5 5	5 0	4 6	5 7	5 2	4 7	4 3	5 0	4 6	4 2	3 9	4 3	4 0	3 7	3 4	2 6
	横方向 (A)		縦方向 (B)	3 . 0	6 3	5 8	5 3	4 9	5 9	5 4	5 0	4 6	5 2	4 8	4 4	4 1	4 5	4 2	3 9	3 7	2 9
H m	1 . 6 5 H m	1 . 6 5 H m	4 . 0	6 6	6 1	5 7	5 4	6 2	5 8	5 4	5 1	5 4	5 1	4 8	4 6	4 7	4 5	4 2	4 0	3 2	
			5 . 0	6 8	6 4	6 0	5 7	6 4	6 0	5 7	5 4	5 6	5 3	5 1	4 8	4 9	4 7	4 5	4 3	3 4	
			7 . 0	7 0	6 7	6 4	6 1	6 6	6 3	6 0	5 8	5 8	5 6	5 4	5 2	5 1	4 9	4 7	4 6	3 7	
			1 0 . 0	7 1	6 9	6 7	6 5	6 7	6 5	6 3	6 1	6 0	5 8	5 6	5 5	5 2	5 1	5 0	4 9	3 9	

