

屋内照明器具特性	
品番 (品名)	L G B 1 9 3 2 5 B F
光源	L D A 7 L - D - G / S / Z 6 × 3 8 1 0 . 0 l m
管理番号	K 0 1 8 9 0 5 5 (1) D R 1
B Z 分類	B Z 1 0 / 8 . 5 / B Z 9

器具効率		8 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
上方光束 下方光束		3 9 % 4 3 %	室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6	3 5	2 5	1 8	1 3	3 2	2 3	1 6	1 2	2 6	1 9	1 4	1 0	2 1	1 5	1 1	8	3	
			0 . 8	4 2	3 2	2 4	1 9	3 8	2 9	2 2	1 8	3 1	2 4	1 9	1 5	2 5	1 9	1 5	1 2	6	
			1 . 0	4 7	3 7	2 9	2 4	4 3	3 4	2 7	2 2	3 5	2 8	2 3	1 8	2 8	2 2	1 8	1 5	8	
			0 . 5 6	1 . 2 5	5 2	4 2	3 5	2 9	4 7	3 8	3 2	2 7	3 9	3 2	2 7	2 2	3 1	2 6	2 2	1 8	1 1
下方投影面積		c m ²	1 . 5	5 5	4 6	3 9	3 3	5 0	4 2	3 6	3 1	4 1	3 5	3 0	2 6	3 3	2 9	2 4	2 1	1 3	
等価発光面積		c m ²	2 . 0	6 0	5 2	4 5	4 0	5 5	4 8	4 2	3 7	4 5	4 0	3 5	3 1	3 7	3 3	2 9	2 6	1 7	
取付 高さ	器具間隔最大限		2 . 5	6 3	5 6	5 0	4 5	5 8	5 1	4 6	4 1	4 8	4 3	3 9	3 5	3 9	3 5	3 2	2 9	1 9	
	横方向 (A) 縦方向 (B)		3 . 0	6 5	5 9	5 3	4 8	6 0	5 4	4 9	4 5	5 0	4 6	4 2	3 8	4 1	3 8	3 5	3 2	2 1	
H m	2 . 6 0 H m	2 . 6 0 H m	4 . 0	6 8	6 3	5 8	5 4	6 3	5 8	5 4	5 0	5 3	4 9	4 6	4 3	4 4	4 1	3 8	3 6	2 5	
			5 . 0	7 0	6 5	6 1	5 7	6 5	6 1	5 7	5 4	5 5	5 2	4 9	4 6	4 6	4 3	4 1	3 8	2 7	
			7 . 0	7 2	6 9	6 5	6 2	6 7	6 4	6 1	5 8	5 7	5 5	5 2	5 0	4 8	4 6	4 4	4 2	3 0	
			1 0 . 0	7 4	7 2	6 9	6 6	6 9	6 7	6 4	6 2	5 9	5 7	5 5	5 3	5 0	4 8	4 7	4 5	3 3	

