

屋内照明器具特性	
品番 (品名)	L G B 1 6 1 3 6
光源	LLD2000CU1 ×1 566.0 lm
管理番号	K0189918 (0) DR 1
B Z 分類	BZ4 / 3.5 / BZ5

器具効率		88 % 上方光束 4 % 下方光束 84 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z CM																
保守率		良 中 否	0.67	0.6	52	41	35	30	50	41	35	30	48	40	34	30	46	38	33	29	28
			0.63	0.8	60	51	44	39	59	50	44	39	56	48	43	39	54	47	42	38	36
			0.56	1.0	66	57	51	46	64	56	50	46	61	54	49	45	59	53	48	44	42
				1.25	71	63	57	52	69	62	56	52	66	60	55	51	63	58	54	50	48
下方投影面積 等価発光面積		cm ²		1.5	74	67	61	57	73	66	60	56	69	64	59	55	66	61	58	54	52
				2.0	79	73	68	63	77	71	67	63	74	69	65	61	71	67	63	60	57
取付 高さ	器具間隔最大限		2.5	82	76	72	68	80	75	71	67	77	72	69	66	73	70	67	64	61	
	横方向 (A) 縦方向 (B)			3.0	84	79	75	71	82	78	74	71	79	75	72	69	76	73	70	67	64
H m	1.26 H m 1.26 H m		4.0	86	82	79	76	84	81	78	75	81	78	76	73	78	76	74	72	68	
			5.0	88	85	82	79	86	83	81	78	83	80	78	76	80	78	76	74	71	
			7.0	90	87	85	83	88	86	84	82	85	83	81	80	82	80	79	77	74	
			10.0	91	89	88	86	89	88	86	85	86	85	84	82	83	82	81	80	76	

