

屋内照明器具特性	
品番 (品名)	L G B 1 0 8 4 6
光源	LLD4000LCE1 ×1 845.0 l m
管理番号	K0191973 (1) DR 1
B Z 分類	BZ4 / 0.7 / BZ3 / 1.1 / BZ4

器具効率		67 %	反射率	天井	80 %				70 %				50 %				30 %				0 %				
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %				10 %				10 %				10 %				0 %				
上方光束		2 %	室指数	照明率 (X0.01)																			Z	C	M
下方光束		65 %																							
保守率		良 中 否	0.67	0.6	41	33	28	25	40	33	28	25	38	32	28	25	37	31	27	25	23				
			0.63	0.8	47	40	36	32	46	40	35	32	44	39	35	32	42	38	34	31	30				
			0.56	1.0	51	45	40	37	50	44	40	37	48	43	39	36	46	42	39	36	34				
				1.25	55	49	45	42	54	49	44	41	52	47	44	41	50	46	43	40	39				
下方投影面積		c m ²		1.5	57	52	48	45	56	51	48	45	54	50	47	44	52	49	46	43	42				
等価発光面積			c m ²	2.0	61	56	53	50	60	55	52	49	57	54	51	49	55	52	50	48	46				
取付 高さ	器具間隔最大限			2.5	63	59	56	53	62	58	55	53	59	56	54	52	57	55	53	51	49				
	横方向 (A)		縦方向 (B)	3.0	64	61	58	56	63	60	57	55	61	58	56	54	59	57	55	53	51				
H m	1.24 H m		1.24 H m	4.0	66	63	61	59	65	62	60	58	63	61	59	57	61	59	57	56	54				
				5.0	67	65	63	61	66	64	62	60	64	62	61	59	62	60	59	58	56				
				7.0	68	67	65	64	67	66	64	63	65	64	63	62	63	62	61	60	58				
				10.0	69	68	67	66	68	67	66	65	66	65	64	63	64	63	63	62	60				

