

屋内照明器具特性

品番 (品名)	LGWC47120										
光源	LLD4000MLCB1 ×1 845.0 lm										
管理番号	K0176340(0)DR1										
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2										

器具効率	59%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	0%																			
下方光束	59%																			
		室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.63 0.6 0.56	0.6	38	32	28	25	38	32	28	25	36	31	28	25	35	31	28	25	24	
		0.8	44	39	35	32	44	38	35	32	42	38	35	32	41	37	34	32	31	
		1.0	48	43	40	37	47	43	39	37	46	42	39	37	45	41	39	36	35	
		1.25	51	47	44	41	51	47	43	41	49	46	43	41	48	45	42	40	39	
下方投影面積	c m ²	1.5	53	50	47	44	53	49	46	44	51	48	46	44	50	47	45	43	42	
		2.0	56	53	50	48	55	52	50	48	54	51	49	47	52	50	49	47	46	
		2.5	58	55	53	51	57	54	52	51	55	53	52	50	54	52	51	49	48	
取付高さ	器具間隔最大限		3.0	59	56	55	53	58	56	54	52	56	55	53	52	55	54	52	51	50
	横方向 (A)	縦方向 (B)	4.0	60	58	57	55	59	58	56	55	58	56	55	54	56	55	54	53	52
H m	1.17H m	1.17H m	5.0	61	59	58	57	60	59	58	56	59	58	57	56	57	56	56	55	53
			7.0	62	61	60	59	61	60	59	58	60	59	58	57	58	58	57	56	55
			10.0	62	62	61	60	62	61	60	60	60	60	59	59	59	58	58	58	56

