

屋内照明器具特性

品番 (品名)	L G W C 4 7 1 2 0	
光源	L L D 2 0 2 0 M L C B 1 × 1 4 6 0 . 0 1 m	
管理番号	K 0 1 7 6 3 4 9 (0) D R 1	
B Z 分類	B Z 1	

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
下方光束	89 %	床	10 %				10 %				10 %				10 %				0 %		
室指数	照明率 (X 0 . 0 1)																			Z C M	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	8.6	8.8	9.0	9.2	9.2	9.3	9.4	9.4	9.5	
	等価発光面積		c m ²	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	8.8	9.0	9.2	9.3	9.4	9.4	9.5	9.5	9.5	9.5
取付高さ	器具間隔最大限																				
	横方向 (A)	縦方向 (B)																			
H m	0.41 H m	0.41 H m	4.0	5.0	7.0	10.0	9.3	9.4	9.5	9.5	9.5	9.4	9.3	9.4	9.4	9.3	9.3	9.2	9.2	9.2	

