

屋内照明器具特性	
品番 (品名)	L G W C 4 7 1 2 1
光源	LLD4000MLCB1 ×1 845.0 l m
管理番号	K0176340(0)DR1
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2

器具効率	59%	天井	80%				70%				50%				30%				0%																																										
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%																																										
		床	10%				10%				10%				10%				0%																																										
上方光束	0%	室指数																				照明率 (X0.01)																				Z C M																			
下方光束	59%																																																												
保守率	良 中 否 0.63 0.6 0.56	0.6	38	32	28	25	38	32	28	25	36	31	28	25	35	31	28	25	24																																										
		0.8	44	39	35	32	44	38	35	32	42	38	35	32	41	37	34	32	31																																										
		1.0	48	43	40	37	47	43	39	37	46	42	39	37	45	41	39	36	35																																										
		1.25	51	47	44	41	51	47	43	41	49	46	43	41	48	45	42	40	39																																										
下方投影面積	c m ²	1.5	53	50	47	44	53	49	46	44	51	48	46	44	50	47	45	43	42																																										
		2.0	56	53	50	48	55	52	50	48	54	51	49	47	52	50	49	47	46																																										
取付高さ	器具間隔最大限		2.5	58	55	53	51	57	54	52	51	55	53	52	50	54	52	51	49	48																																									
	横方向 (A)	縦方向 (B)	3.0	59	56	55	53	58	56	54	52	56	55	53	52	55	54	52	51	50																																									
H m	1.17 H m	1.17 H m	4.0	60	58	57	55	59	58	56	55	58	56	55	54	56	55	54	53	52																																									
			5.0	61	59	58	57	60	59	58	56	59	58	57	56	57	56	56	55	53																																									
			7.0	62	61	60	59	61	60	59	58	60	59	58	57	58	58	57	56	55																																									
			10.0	62	62	61	60	62	61	60	60	60	60	59	59	59	58	58	58	58	56																																								

