

屋内照明器具特性	
品番 (品名)	LGWC47122
光源	LLD4000MLCB1 ×1 845.0 lm
管理番号	K0176340(0)DR1
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2

器具効率	59%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	0%	室指数	照明率 (X0.01)																ZCM	
下方光束	59%																			
保守率	良	0.63	0.6	3.8	3.2	2.8	2.5	3.8	3.2	2.8	2.5	3.6	3.1	2.8	2.5	3.5	3.1	2.8	2.5	2.4
	中	0.6	0.8	4.4	3.9	3.5	3.2	4.4	3.8	3.5	3.2	4.2	3.8	3.5	3.2	4.1	3.7	3.4	3.2	3.1
	否	0.56	1.0	4.8	4.3	4.0	3.7	4.7	4.3	3.9	3.7	4.6	4.2	3.9	3.7	4.5	4.1	3.9	3.6	3.5
			1.25	5.1	4.7	4.4	4.1	5.1	4.7	4.3	4.1	4.9	4.6	4.3	4.1	4.8	4.5	4.2	4.0	3.9
下方投影面積		cm ²	1.5	5.3	5.0	4.7	4.4	5.3	4.9	4.6	4.4	5.1	4.8	4.6	4.4	5.0	4.7	4.5	4.3	4.2
等価発光面積		cm ²	2.0	5.6	5.3	5.0	4.8	5.5	5.2	5.0	4.8	5.4	5.1	4.9	4.7	5.2	5.0	4.9	4.7	4.6
取付高さ	器具間隔最大限		2.5	5.8	5.5	5.3	5.1	5.7	5.4	5.2	5.1	5.5	5.3	5.2	5.0	5.4	5.2	5.1	4.9	4.8
	横方向 (A)	縦方向 (B)	3.0	5.9	5.6	5.5	5.3	5.8	5.6	5.4	5.2	5.6	5.5	5.3	5.2	5.5	5.4	5.2	5.1	5.0
Hm	1.17Hm	1.17Hm	4.0	6.0	5.8	5.7	5.5	5.9	5.8	5.6	5.5	5.8	5.6	5.5	5.4	5.6	5.5	5.4	5.3	5.2
			5.0	6.1	5.9	5.8	5.7	6.0	5.9	5.8	5.6	5.9	5.8	5.7	5.6	5.7	5.6	5.6	5.5	5.3
			7.0	6.2	6.1	6.0	5.9	6.1	6.0	5.9	5.8	6.0	5.9	5.8	5.7	5.8	5.8	5.7	5.6	5.5
			10.0	6.2	6.2	6.1	6.0	6.2	6.1	6.0	6.0	6.0	6.0	5.9	5.9	5.9	5.8	5.8	5.8	5.6

