

屋内照明器具特性	
品番 (品名)	L G W C 4 7 1 2 2
光源	LLD2020LCB1 x1 460.0 l m
管理番号	K0176348 (0) DR 1
B Z 分類	B Z 1

器具効率	91 %	天井	80 %				70 %				50 %				30 %				0 %					
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %					
下方光束	91 %		室指数	照明率 (X 0 . 0 1)																Z C M				
保守率	良 0.63	0.6	0.6	77	72	69	66	77	72	69	66	76	71	68	66	75	71	68	66	65				
	中 0.6	0.6	0.8	83	78	75	72	82	78	75	72	81	77	74	72	79	76	74	72	71				
	否 0.56	0.6	1.0	86	82	79	76	85	81	78	76	84	80	78	76	82	79	77	76	74				
下方投影面積	c m ²	等価発光面積	c m ²	1.25	89	85	82	80	88	84	82	80	86	83	81	79	85	82	80	79	77			
				1.5	90	87	84	82	89	86	84	82	88	85	83	82	86	84	82	81	80			
取付高さ	器具間隔最大限		H m	0.41 H m	H m	0.41 H m	2.5	94	92	90	88	93	91	89	88	91	89	88	87	89	88	87	86	84
	横方向 (A)	縦方向 (B)					3.0	95	93	91	90	94	92	90	89	92	90	89	88	90	89	88	87	85
						4.0	96	94	93	92	95	93	92	91	93	92	91	90	91	90	89	89	86	
						5.0	96	95	94	93	95	94	93	92	93	92	92	91	92	91	90	90	87	
						7.0	97	96	95	94	96	95	94	94	94	93	93	92	92	92	91	91	88	
						10.0	98	97	96	96	97	96	95	95	95	94	94	93	93	92	92	89		

