

屋内照明器具特性

品番 (品名)	XAD1230L	
光源	LED2700_70_440 ×1	440.0 lm
管理番号	K0165463(0)DB1	
BZ分類	BZ1	

器具効率	101%	天井	80%				70%				50%				30%				0%	
	上方光束 0%		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
下方光束	101%	床		10%				10%				10%				10%				0%
室指数	照明率 (X0.01)																			ZCM
保守率	良 0.67	0.6	84	77	73	71	83	77	73	71	82	76	73	70	80	76	73	70	69	
	中 0.63		90	84	80	78	89	84	80	78	87	83	80	77	86	82	79	77	76	
	否 0.56		94	89	85	82	93	88	85	82	91	87	84	82	89	86	83	81	80	
下方投影面積	cm ²	1.25	97	92	89	86	96	92	89	86	94	90	88	86	92	89	87	85	84	
		1.5	99	95	92	89	98	94	91	89	96	93	90	88	94	92	90	88	86	
等価発光面積	cm ²	2.0	101	98	96	93	100	97	95	93	98	96	94	92	96	94	93	91	90	
		2.5	103	100	98	96	102	99	97	96	100	98	96	94	98	96	95	93	92	
器具間隔最大限	高さ		3.0	104	102	100	98	103	101	99	97	101	99	97	96	99	97	96	93	
	横方向 (A)	縦方向 (B)	4.0	105	103	102	100	104	102	101	100	102	101	99	98	100	99	98	95	
Hm	0.40Hm	0.40Hm	5.0	106	104	103	102	105	103	102	101	103	102	101	100	101	100	99	96	
			7.0	107	106	105	104	106	105	104	103	103	103	102	101	101	101	100	97	
			10.0	107	107	106	105	106	106	105	104	104	103	103	102	102	101	101	98	

