

# 屋内照明器具特性

品番 (品名)	L G W C 4 7 1 2 3														
光源	LLD2000MLCB1 ×1 531.0 l m														
管理番号	K0176342 ( 0 ) DR 1														
B Z 分類	B Z 3 / 0 . 9 / B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2														

器具効率	62 %	天井	80 %				70 %				50 %				30 %				0 %			
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束	0 %	室指数	照明率 ( X 0 . 0 1 )																			Z C M
下方光束	62 %																					
保守率	良 中 否 0.63 0.6 0.56	0.6	40	34	30	27	39	33	29	27	38	33	29	27	37	32	29	27	25			
		0.8	47	41	37	34	46	40	37	34	44	40	36	34	43	39	36	34	32			
		1.0	51	45	42	39	50	45	41	39	48	44	41	39	47	43	41	38	37			
		1.25	54	49	46	43	53	49	46	43	52	48	45	43	50	47	45	43	41			
下方投影面積	c m <sup>2</sup>	1.5	56	52	49	46	55	51	49	46	54	50	48	46	52	50	47	45	44			
		2.0	59	56	53	51	58	55	53	50	56	54	52	50	55	53	51	49	48			
取付高さ	器具間隔最大限		2.5	61	58	55	53	60	57	55	53	58	56	54	53	57	55	53	51			
	横方向 ( A )	縦方向 ( B )	3.0	62	59	57	55	61	59	57	55	59	57	56	54	58	56	55	54	52		
H m	1.17 H m	1.17 H m	4.0	63	61	60	58	62	61	59	58	61	59	58	57	59	58	57	56	55		
			5.0	64	62	61	60	63	62	60	59	62	60	59	58	60	59	58	58	56	56	
			7.0	65	64	63	62	64	63	62	61	63	62	61	60	61	60	60	59	58		
			10.0	66	65	64	63	65	64	63	63	63	63	62	62	62	61	61	60	59		

