

屋内照明器具特性	
品番 (品名)	L G W C 4 7 1 2 3
光源	LLD3020LCB1 ×1 795.0 l m
管理番号	K0176345 (0) DR 1
B Z 分類	B Z 1

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	89 %	床	10 %				10 %				10 %				10 %				0 %	
室指数		照明率 (X 0.01)	Z C M																	
保守率	良 0.63	0.6	0.6	76	70	67	65	75	70	67	65	74	70	67	65	73	69	66	65	64
	中 0.6	0.8	0.8	81	76	73	71	80	76	73	71	79	75	72	70	78	74	72	70	69
	否 0.56	1.0	1.0	84	80	77	75	83	79	77	75	82	79	76	74	81	78	76	74	73
下方投影面積	c m ²	1.25	87	83	80	78	86	82	80	78	84	81	79	77	83	80	79	77	76	
		1.5	88	85	83	81	87	84	82	80	86	83	81	80	84	82	81	79	78	
等価発光面積	c m ²	2.0	90	88	86	84	90	87	85	84	88	86	84	83	86	85	83	82	80	
		2.5	92	89	88	86	91	89	87	86	89	87	86	85	87	86	85	84	82	
取付高さ	器具間隔最大限		3.0	93	91	89	88	92	90	88	87	90	88	87	86	88	87	86	85	83
H m	横方向 (A)	縦方向 (B)	4.0	94	92	91	90	93	91	90	89	91	90	89	88	89	88	87	87	85
	0.41 H m	0.41 H m	5.0	94	93	92	91	93	92	91	90	91	90	90	89	90	89	88	88	85
			7.0	95	94	93	92	94	93	92	92	92	91	91	90	90	89	89	86	
			10.0	95	95	94	94	94	94	93	93	92	92	92	91	91	90	90	87	

