

屋内照明器具特性

品番 (品名)	L G W C 4 7 1 2 4				
光源	L L D 2 0 0 0 M L C B 1 × 1 5 3 1 . 0 l m				
管理番号	K 0 1 7 6 3 4 2 (0) D R 1				
B Z 分類	B Z 3 / 0 . 9 / B Z 2 / 4 . 5 / B Z 3 / 6 . 0 / B Z 2				

器具効率	62 %	天井	80 %				70 %				50 %				30 %				0 %				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %				
下方光束	62 %	室指数	照明率 (X 0 . 0 1)																				Z C M
保守率	良	0.63	0.6	40	34	30	27	39	33	29	27	38	33	29	27	37	32	29	27	25			
	中	0.6	0.8	47	41	37	34	46	40	37	34	44	40	36	34	43	39	36	34	32			
	否	0.56	1.0	51	45	42	39	50	45	41	39	48	44	41	39	47	43	41	38	37			
			1.25	54	49	46	43	53	49	46	43	52	48	45	43	50	47	45	43	41			
下方投影面積	c m ²		1.5	56	52	49	46	55	51	49	46	54	50	48	46	52	50	47	45	44			
等価発光面積	c m ²		2.0	59	56	53	51	58	55	53	50	56	54	52	50	55	53	51	49	48			
取付高さ	器具間隔最大限		2.5	61	58	55	53	60	57	55	53	58	56	54	53	57	55	53	52	51			
	横方向 (A)	縦方向 (B)	3.0	62	59	57	55	61	59	57	55	59	57	56	54	58	56	55	54	52			
H m	1.17 H m	1.17 H m	4.0	63	61	60	58	62	61	59	58	61	59	58	57	59	58	57	56	55			
			5.0	64	62	61	60	63	62	60	59	62	60	59	58	60	59	58	58	56			
			7.0	65	64	63	62	64	63	62	61	63	62	61	60	61	60	60	59	58			
			10.0	66	65	64	63	65	64	63	63	63	63	62	62	62	61	61	60	59			

