

屋内照明器具特性	
品番(品名)	L G W C 4 7 1 2 4
光源	L L D 2 0 2 0 L C B 1 × 1 4 6 0 . 0 1 m
管理番号	K 0 1 7 6 3 4 8 (0) D R 1
B Z 分類	B Z 1

器具効率	91 %	天井	80 %				70 %				50 %				30 %				0 %		
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10			
上方光束	0 %	反射率	壁	10 %				10 %				10 %				10 %				0 %	
下方光束	91 %		床	10 %				10 %				10 %				10 %				0 %	
		室指数	照明率 (X 0 . 0 1)																Z C M		
保守率	良 0.63	0.6	0.6	77	72	69	66	77	72	69	66	76	71	68	66	75	71	68	66	65	
	中 0.6			0.8	83	78	75	72	82	78	75	72	81	77	74	72	79	76	74	72	71
	否 0.56			1.0	86	82	79	76	85	81	78	76	84	80	78	76	82	79	77	76	74
下方投影面積	c m ²	1.25	89	85	82	80	88	84	82	80	86	83	81	79	85	82	80	79	77		
		1.5	90	87	84	82	89	86	84	82	88	85	83	82	86	84	82	81	80		
等価発光面積	c m ²	2.0	92	90	88	86	92	89	87	85	90	88	86	85	88	87	85	84	82		
		2.5	94	92	90	88	93	91	89	88	91	89	88	87	89	88	87	86	84		
取付高さ	器具間隔最大限		H m	0.41	95	93	91	90	94	92	90	89	92	90	89	88	90	89	88	87	85
	横方向(A)	縦方向(B)		0.41	96	94	93	92	95	93	92	91	93	92	91	90	91	90	89	89	86
			H m	5.0	96	95	94	93	95	94	93	92	93	92	92	91	92	91	90	90	87
				7.0	97	96	95	94	96	95	94	94	94	93	93	92	92	92	91	91	88
				10.0	98	97	96	96	97	96	95	95	95	94	94	93	93	92	92	92	89

