

# 屋内照明器具特性

|         |                 |          |
|---------|-----------------|----------|
| 品番 (品名) | LGWC47124       |          |
| 光源      | LLD2020MLCB1 ×1 | 460.0 lm |
| 管理番号    | K0176349(0)DR1  |          |
| BZ分類    | BZ1             |          |

|                  |                 |         |                |                    |                |                    |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
|------------------|-----------------|---------|----------------|--------------------|----------------|--------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 器具効率             | 89%             | 天井      | 80%            |                    |                |                    | 70%  |      |      |      | 50%  |      |      |      | 30%  |      |      |      | 0%   |      |
|                  | 上方光束            |         | 0%             | 70                 | 50             | 30                 | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 0%   |
| 下方光束             | 89%             | 床       | 10%            |                    |                |                    | 10%  |      |      |      | 10%  |      |      |      | 10%  |      |      |      | 0%   |      |
| 室指数              | 照明率 ( X0.01 )   |         |                |                    |                |                    |      |      |      |      |      |      |      |      |      |      |      |      |      | ZCM  |
| 保守率              | 良               | 0.63    | 0.6            | 0.6                | 0.6            | 0.6                | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  |
|                  | 中               | 0.6     | 0.6            | 0.6                | 0.6            | 0.6                | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  | 0.6  |
|                  | 否               | 0.56    | 0.56           | 0.56               | 0.56           | 0.56               | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 | 0.56 |
| 下方投影面積<br>等価発光面積 | cm <sup>2</sup> | 1.25    | 1.5            | 2.0                | 2.5            | 3.0                | 4.0  | 5.0  | 7.0  | 10.0 | 8.6  | 8.8  | 9.0  | 9.2  | 9.3  | 9.4  | 9.5  | 9.5  | 9.5  | 9.5  |
|                  |                 | 1.5     | 2.0            | 2.5                | 3.0            | 4.0                | 5.0  | 7.0  | 10.0 | 8.8  | 9.0  | 9.2  | 9.3  | 9.4  | 9.5  | 9.5  | 9.5  | 9.5  | 9.5  | 9.5  |
|                  |                 | 2.0     | 2.5            | 3.0                | 4.0            | 5.0                | 7.0  | 10.0 | 9.0  | 9.2  | 9.3  | 9.4  | 9.5  | 9.5  | 9.5  | 9.5  | 9.5  | 9.5  | 9.5  | 9.5  |
| 取付高さ             | 器具間隔最大限         |         | H <sub>m</sub> | 0.41H <sub>m</sub> | H <sub>m</sub> | 0.41H <sub>m</sub> | 2.5  | 3.0  | 4.0  | 5.0  | 7.0  | 10.0 | 9.2  | 9.3  | 9.4  | 9.5  | 9.5  | 9.5  | 9.5  | 9.5  |
|                  | 横方向 (A)         | 縦方向 (B) |                |                    |                |                    | 3.0  | 4.0  | 5.0  | 7.0  | 10.0 | 9.3  | 9.4  | 9.5  | 9.5  | 9.5  | 9.5  | 9.5  | 9.5  | 9.5  |

