

# 屋内照明器具特性

品番 (品名)	L G W C 4 7 1 2 5														
光源	LLD4000LCB1 ×1                      845.0 1 m														
管理番号	K0176339 ( 0 ) DR 1														
B Z 分類	B Z 3 / 0.9 / B Z 2 / 4.5 / B Z 3 / 6.0 / B Z 2														

器具効率	64 %	天井	80 %				70 %				50 %				30 %				0 %		
			反射率	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束	0 %	室指数	照明率 ( X 0.01 )															Z C M			
下方光束	64 %																				
保守率	良 0.63 中 0.6 否 0.56	0.6	41	35	30	27	41	34	30	27	39	34	30	27	38	33	30	27	26		
		0.8	48	42	38	35	47	42	38	35	46	41	37	35	44	40	37	35	33		
		1.0	52	47	43	40	51	46	43	40	50	45	42	40	48	45	42	39	38		
		1.25	55	51	47	45	55	50	47	44	53	49	46	44	52	48	46	44	43		
下方投影面積	c m <sup>2</sup>	1.5	58	54	50	48	57	53	50	47	55	52	49	47	54	51	49	47	45		
		2.0	61	57	54	52	60	57	54	52	58	55	53	51	57	54	52	51	49		
取付高さ	器具間隔最大限		2.5	62	59	57	55	61	59	57	55	60	58	56	54	58	56	55	53	52	
	横方向 ( A )	縦方向 ( B )	3.0	63	61	59	57	63	60	58	57	61	59	57	56	60	58	57	55	54	
H m	1.17 H m	1.17 H m	4.0	65	63	61	60	64	62	61	59	62	61	60	58	61	60	59	58	56	
			5.0	66	64	63	61	65	63	62	61	63	62	61	60	62	61	60	59	58	
			7.0	67	66	64	64	66	65	64	63	64	63	63	62	63	62	62	61	59	
			10.0	67	67	66	65	67	66	65	64	65	65	64	63	64	63	63	62	60	

