

屋内照明器具特性

品番 (品名)	LGWC47125											
光源	LLD4000MLCB1 ×1						845.0 l m					
管理番号	K0176340(0)DR1											
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2											

器具効率	59%	天井		80%				70%				50%				30%				0%		
		壁	床	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
上方光束	0%																					
下方光束	59%																					
		室指数																				
		照明率 (X0.01) ZCM																				
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	c m ²	1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	
		等価発光面積	c m ²	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0
取付高さ	器具間隔最大限		H m	1.17 H m	1.17 H m	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15.0	20.0	25.0	30.0	40.0	50.0	60.0	70.0	8.0	10.0
	横方向 (A)	縦方向 (B)																				

