

屋内照明器具特性

品番 (品名)	L G W C 4 7 1 2 5	
光源	LLD2020MLCB1 ×1	460.0 1m
管理番号	K0176349 (0) DR 1	
BZ分類	BZ1	

器具効率	89 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束		0 %	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	89 %	床	10 %				10 %				10 %				10 %				0 %	
室指数	照明率 (X 0.01)																			ZCM
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56
下方投影面積	c m ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	7.0	10.0	8.6	8.8	9.0	9.2	9.2	9.3	9.4	9.4	9.5
	等価発光面積		c m ²	8.6	8.8	9.0	9.2	9.2	9.3	9.4	9.5	8.3	8.5	8.8	8.9	8.9	9.1	9.1	9.2	9.2
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	7.0	10.0	9.2	9.2	9.3	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2	9.2
	横方向 (A)	縦方向 (B)	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m	0.41H _m

