

屋内照明器具特性	
品番 (品名)	LGWC47126
光源	LLD4000LCB1 ×1 845.0 lm
管理番号	K0176339(0)DR1
BZ分類	BZ3/0.9/BZ2/4.5/BZ3/6.0/BZ2

器具効率	64%	天井	80%				70%				50%				30%				0%		
	上方光束		0%	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
	下方光束		64%		床	10%				10%				10%				10%			
室指数	照明率 (X0.01)																			ZCM	
保守率	良	0.63	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	中	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6	
	否	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	0.56	
下方投影面積	cm ²		1.25	1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15	20	25	30	40	50	
	等価発光面積		1.5	2.0	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15	20	25	30	40	50	60	
取付高さ	器具間隔最大限		2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15	20	25	30	40	50	60	70	80	
	横方向 (A)	縦方向 (B)	3.0	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15	20	25	30	40	50	60	70	80	10.0	
Hm	1.17Hm	1.17Hm	4.0	5.0	6.0	7.0	8.0	10.0	12.5	15	20	25	30	40	50	60	70	80	10.0	12.5	
			5.0	6.0	7.0	8.0	10.0	12.5	15	20	25	30	40	50	60	70	80	10.0	12.5	15	
			7.0	8.0	10.0	12.5	15	20	25	30	40	50	60	70	80	10.0	12.5	15	20	25	
			10.0	12.5	15	20	25	30	40	50	60	70	80	10.0	12.5	15	20	25	30	40	

