

屋内照明器具特性	
品番(品名)	L G W C 4 7 1 2 7
光源	LLD2020MLCB1 ×1 460.0 1m
管理番号	K0176349(0)DR1
BZ分類	BZ1

器具効率	89%	反射率	天井	80%				70%				50%				30%				0%
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	89%	室指数	照明率 (X 0.01)																ZCM	
保守率	良 0.63	0.6	0.6	76	70	67	65	75	70	67	65	74	69	67	65	73	69	66	64	64
	中 0.6	0.6	0.8	81	76	73	71	80	76	73	71	79	75	72	70	77	74	72	70	69
	否 0.56	0.6	1.0	84	80	77	75	83	79	76	74	82	78	76	74	80	78	75	74	73
下方投影面積	cm ²	1.25	86	83	80	78	86	82	80	78	84	81	79	77	83	80	78	77	76	
		1.5	88	85	82	80	87	84	82	80	86	83	81	80	84	82	80	79	78	
等価発光面積	cm ²	2.0	90	88	86	84	89	87	85	83	88	86	84	83	86	84	83	82	80	
		2.5	92	89	87	86	91	89	87	85	89	87	86	84	87	86	85	84	82	
取付高さ	器具間隔最大限		3.0	92	90	89	87	91	90	88	87	90	88	87	86	88	87	86	85	83
Hm	横方向(A)	縦方向(B)	4.0	93	92	91	89	92	91	90	89	91	89	88	88	89	88	87	86	84
	0.41Hm	0.41Hm	5.0	94	93	92	91	93	92	91	90	91	90	89	89	89	89	88	87	85
			7.0	95	94	93	92	94	93	92	91	92	91	91	90	90	89	89	88	86
			10.0	95	95	94	93	94	94	93	93	92	92	91	91	90	90	90	89	87

