

# 屋内照明器具特性

|         |                     |           |
|---------|---------------------|-----------|
| 品番 (品名) | LGS3300N            |           |
| 光源      | LED5000_70_722.5 ×2 | 722.5 1 m |
| 管理番号    | K0157851(0)DB1      |           |
| BZ分類    | BZ4                 |           |

|        |         |                 |              |      |      |      |      |      |      |      |      |      |      |     |     |     |     |     |     |     |
|--------|---------|-----------------|--------------|------|------|------|------|------|------|------|------|------|------|-----|-----|-----|-----|-----|-----|-----|
| 器具効率   | 100%    | 天井              | 80%          |      |      |      | 70%  |      |      |      | 50%  |      |      |     | 30% |     |     |     | 0%  |     |
|        |         | 壁               | 70           | 50   | 30   | 10   | 70   | 50   | 30   | 10   | 70   | 50   | 30   | 10  | 70  | 50  | 30  | 10  | 0%  |     |
| 上方光束   | 0%      | 床               | 10%          |      |      |      | 10%  |      |      |      | 10%  |      |      |     | 10% |     |     |     | 0%  |     |
| 下方光束   | 100%    | 室指数             | 照明率 ( X0.01) |      |      |      |      |      |      |      |      |      |      |     |     |     |     |     | ZCM |     |
| 保守率    | 良       | 0.67            | 0.6          | 5.9  | 4.8  | 4.0  | 3.5  | 5.8  | 4.7  | 4.0  | 3.5  | 5.6  | 4.6  | 3.9 | 3.5 | 5.4 | 4.5 | 3.9 | 3.5 | 3.3 |
|        | 中       | 0.63            | 0.8          | 7.0  | 5.9  | 5.1  | 4.6  | 6.8  | 5.8  | 5.1  | 4.6  | 6.6  | 5.7  | 5.1 | 4.6 | 6.3 | 5.6 | 5.0 | 4.6 | 4.4 |
|        | 否       | 0.56            | 1.0          | 7.6  | 6.7  | 5.9  | 5.4  | 7.5  | 6.6  | 5.9  | 5.4  | 7.2  | 6.4  | 5.8 | 5.4 | 7.0 | 6.3 | 5.7 | 5.3 | 5.1 |
|        |         |                 | 1.25         | 8.2  | 7.4  | 6.7  | 6.2  | 8.1  | 7.3  | 6.7  | 6.2  | 7.8  | 7.1  | 6.6 | 6.1 | 7.5 | 6.9 | 6.5 | 6.1 | 5.9 |
| 下方投影面積 |         | cm <sup>2</sup> | 1.5          | 8.6  | 7.9  | 7.2  | 6.8  | 8.5  | 7.8  | 7.2  | 6.7  | 8.2  | 7.6  | 7.1 | 6.7 | 7.9 | 7.4 | 7.0 | 6.6 | 6.4 |
| 等価発光面積 |         | cm <sup>2</sup> | 2.0          | 9.2  | 8.5  | 8.0  | 7.6  | 9.0  | 8.4  | 7.9  | 7.5  | 8.8  | 8.2  | 7.8 | 7.5 | 8.5 | 8.1 | 7.7 | 7.4 | 7.1 |
| 取付高さ   | 器具間隔最大限 |                 | 2.5          | 9.5  | 9.0  | 8.5  | 8.1  | 9.4  | 8.9  | 8.4  | 8.1  | 9.1  | 8.7  | 8.3 | 8.0 | 8.8 | 8.5 | 8.2 | 7.9 | 7.6 |
|        | 横方向 (A) | 縦方向 (B)         | 3.0          | 9.7  | 9.3  | 8.9  | 8.5  | 9.6  | 9.2  | 8.8  | 8.5  | 9.3  | 9.0  | 8.6 | 8.3 | 9.1 | 8.8 | 8.5 | 8.2 | 8.0 |
| Hm     | 1.21Hm  | 1.22Hm          | 4.0          | 10.0 | 9.6  | 9.3  | 9.0  | 9.9  | 9.5  | 9.2  | 9.0  | 9.6  | 9.3  | 9.1 | 8.8 | 9.4 | 9.1 | 8.9 | 8.7 | 8.5 |
|        |         |                 | 5.0          | 10.2 | 9.9  | 9.6  | 9.4  | 10.0 | 9.8  | 9.5  | 9.3  | 9.8  | 9.6  | 9.3 | 9.1 | 9.5 | 9.3 | 9.2 | 9.0 | 8.7 |
|        |         |                 | 7.0          | 10.4 | 10.1 | 9.9  | 9.8  | 10.2 | 10.0 | 9.8  | 9.7  | 10.0 | 9.8  | 9.7 | 9.5 | 9.7 | 9.6 | 9.5 | 9.3 | 9.1 |
|        |         |                 | 10.0         | 10.5 | 10.3 | 10.2 | 10.1 | 10.4 | 10.2 | 10.1 | 10.0 | 10.1 | 10.0 | 9.9 | 9.8 | 9.9 | 9.8 | 9.7 | 9.6 | 9.3 |

