

屋内照明器具特性	
品番 (品名)	L G B 8 1 6 4 9
光源	LDA4 WW- H- E17 / S / 4 ×1 440.0 lm
管理番号	K0187732 (0) DB 1
BZ分類	BZ5 / 1.1 / BZ4

器具効率		61 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) ZCM																				
保守率		良 中 否	0.67	0.6	34	27	22	18	33	26	22	18	32	26	21	18	31	25	21	18	17				
			0.63	0.8	41	34	29	25	40	33	29	25	38	32	28	25	37	32	28	25	24				
			0.56	1.0	45	39	34	30	44	38	34	30	42	37	33	30	41	36	33	30	29				
				1.25	49	43	39	36	48	43	39	35	46	42	38	35	45	41	37	35	33				
下方投影面積 等価発光面積		cm ²		1.5	52	47	43	39	51	46	42	39	49	45	42	39	47	44	41	38	37				
			cm ²	2.0	55	51	48	45	55	51	47	45	53	49	47	44	51	48	46	44	42				
取付 高さ	器具間隔最大限			2.5	58	54	51	49	57	53	51	48	55	52	50	48	53	51	49	47	46				
	横方向 (A) 縦方向 (B)			3.0	59	56	53	51	58	55	53	51	56	54	52	50	55	53	51	49	48				
H _m	1.36 H _m	1.36 H _m		4.0	61	59	56	55	60	58	56	54	58	57	55	53	57	55	54	53	51				
				5.0	62	60	58	57	61	59	58	56	60	58	57	55	58	57	56	55	53				
				7.0	63	62	61	59	62	61	60	59	61	60	59	58	59	59	58	57	55				
				10.0	64	63	62	61	63	62	62	61	62	61	60	60	60	60	59	59	57				

