

屋内照明器具特性

品番 (品名)

XLGE5030SU

光源

LDA4L-H-E17/S/4 x1 440.0lm

管理番号

K0158856(0)DB1

BZ分類

BZ10

器具効率

64%

上方光束

39%

下方光束

25%

天井
壁
床

80%

70%

50%

30%

0%

室指数

照明率 (X0.01)

ZCM

保守率

良
中
否

0.63

0.6

0.56

下方投影面積

cm²

等価発光面積

cm²

取付

器具間隔最大限

高さ

横方向 (A)

縦方向 (B)

Hm

0.00Hm

0.00Hm

0.6

0.8

1.0

1.25

1.5

2.0

2.5

3.0

4.0

5.0

7.0

10.0

2.7

3.2

3.6

3.9

4.2

4.6

4.8

5.1

5.2

5.5

5.7

1.9

2.4

2.8

3.2

3.5

3.8

4.1

4.4

4.7

5.0

5.1

5.2

5.5

5.7

1.3

1.7

2.1

2.5

2.9

3.3

3.7

4.1

4.5

4.9

5.3

5.6

6.0

6.4

6.8

7.2

7.6

8.0

8.4

8.8

9.2

9.6

10.0

10.4

10.8

11.2

11.6

12.0

12.4

12.8

13.2

13.6

14.0

14.4

14.8

15.2

15.6

16.0

16.4

16.8

17.2

17.6

18.0

18.4

18.8

19.2

19.6

20.0

20.4

20.8

21.2

21.6

22.0

22.4

22.8

23.2

23.6

24.0

24.4

24.8

25.2

25.6

26.0

26.4

26.8

27.2

27.6

28.0

28.4

28.8

29.2

29.6

30.0

30.4

30.8

31.2

31.6

32.0

32.4

32.8

33.2

33.6

34.0

34.4

34.8

35.2

35.6

36.0

36.4

36.8

37.2

37.6

38.0

38.4

38.8

39.2

39.6

40.0

40.4

40.8

41.2

41.6

42.0

42.4

42.8

43.2

43.6

44.0

44.4

44.8

45.2

45.6

46.0

46.4

46.8

47.2

47.6

48.0

48.4

48.8

49.2

49.6

50.0

50.4

50.8

51.2

51.6

52.0

52.4

52.8

53.2

53.6

54.0

54.4

54.8

55.2

55.6

56.0

56.4

56.8

57.2

57.6

58.0

58.4

58.8

59.2

59.6

60.0

60.4

60.8

61.2

61.6

62.0

62.4

62.8

63.2

63.6

64.0

64.4

64.8

65.2

65.6

66.0

66.4

66.8

67.2

67.6

68.0

68.4

68.8

69.2

69.6

70.0

70.4

70.8

71.2

71.6

72.0

72.4

72.8

73.2

73.6

74.0

74.4

74.8

75.2

75.6

76.0

76.4

76.8

77.2

77.6

78.0

78.4

78.8

79.2

79.6

80.0

80.4

80.8

81.2

81.6

82.0

82.4

82.8

83.2

83.6

84.0

84.4

84.8

85.2

85.6

86.0

86.4

86.8