

屋内照明器具特性

品番 (品名)	XLGE5040BU																
光源	LDA4L-H-E17/S/4 x1 440.0lm																
管理番号	K0158855(0)DB1																
BZ分類	BZ10																

器具効率	46%	天井	80%				70%				50%				30%				0%
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	22%	反射率	壁																
下方光束	24%		床	10%				10%				10%				10%			
保守率	良 0.63 中 0.6 否 0.56	室指数	照明率 (X0.01) ZCM																
下方投影面積	cm ²	0.6	1.9	1.3	0.9	0.7	1.8	1.2	0.9	0.6	1.4	1.0	0.7	0.5	1.1	0.8	0.5	0.4	0.1
等価発光面積	cm ²	0.8	2.3	1.7	1.3	1.0	2.1	1.5	1.2	0.9	1.7	1.3	1.0	0.7	1.3	1.0	0.7	0.6	0.2
取付高さ	器具間隔最大限		1.0	2.6	2.0	1.6	1.2	2.3	1.8	1.4	1.1	1.9	1.5	1.2	0.9	1.5	1.2	0.9	0.4
	横方向 (A)	縦方向 (B)	1.25	2.8	2.3	1.9	1.5	2.6	2.1	1.7	1.4	2.1	1.7	1.4	1.1	1.6	1.3	1.1	0.5
Hm	0.00Hm	0.00Hm	1.5	3.0	2.5	2.1	1.8	2.7	2.3	1.9	1.6	2.2	1.9	1.6	1.3	1.8	1.5	1.1	0.6
			2.0	3.3	2.8	2.5	2.1	3.0	2.6	2.3	2.0	2.5	2.1	1.9	1.6	2.0	1.7	1.5	0.8
			2.5	3.5	3.1	2.7	2.4	3.2	2.8	2.5	2.2	2.6	2.3	2.1	1.9	2.1	1.9	1.7	0.9
			3.0	3.6	3.2	2.9	2.6	3.3	3.0	2.7	2.4	2.7	2.5	2.2	2.0	2.2	2.0	1.8	1.1
			4.0	3.8	3.5	3.2	2.9	3.5	3.2	2.9	2.7	2.9	2.7	2.5	2.3	2.4	2.2	2.0	1.2
			5.0	3.9	3.6	3.4	3.1	3.6	3.3	3.1	2.9	3.0	2.8	2.6	2.5	2.5	2.3	2.2	1.4
			7.0	4.0	3.8	3.6	3.4	3.7	3.5	3.4	3.2	3.1	3.0	2.8	2.7	2.6	2.5	2.4	1.6
			10.0	4.1	4.0	3.8	3.7	3.8	3.7	3.5	3.4	3.3	3.1	3.0	2.9	2.7	2.6	2.5	1.7

