

屋内照明器具特性	
品番 (品名)	L G W8 5 0 3 7 W
光源	L D A 4 L - H - E 1 7 / S / 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 2 3 4 0 3 (1) D B 1
B Z 分類	B Z 9 / 3 . 5 / B Z 8

器具効率		5 7 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束		2 4 %	室指数	照明率 (X 0 . 0 1)																		Z C M
下方光束		3 3 %																				
保守率		良	0 . 6 3	0 . 6	2 5	1 8	1 3	1 0	2 3	1 6	1 2	9	1 9	1 4	1 0	8	1 6	1 1	8	6	4	
		中	0 . 6	0 . 8	3 0	2 3	1 8	1 4	2 7	2 1	1 6	1 3	2 3	1 8	1 4	1 1	1 9	1 5	1 2	9	6	
		否	0 . 5 6	1 . 0	3 3	2 6	2 1	1 7	3 1	2 4	2 0	1 6	2 6	2 1	1 7	1 4	2 1	1 7	1 4	1 2	8	
下方投影面積		c m ²		1 . 2 5	3 6	3 0	2 5	2 1	3 4	2 8	2 3	2 0	2 8	2 4	2 0	1 7	2 3	2 0	1 7	1 4	1 0	
等価発光面積		c m ²		1 . 5	3 9	3 3	2 8	2 4	3 6	3 0	2 6	2 2	3 0	2 6	2 2	1 9	2 5	2 2	1 9	1 6	1 1	
				2 . 0	4 2	3 7	3 2	2 9	3 9	3 4	3 0	2 7	3 3	2 9	2 6	2 3	2 7	2 4	2 2	2 0	1 4	
取付高さ	器具間隔最大限			2 . 5	4 4	3 9	3 5	3 2	4 1	3 7	3 3	3 0	3 5	3 1	2 9	2 6	2 9	2 7	2 4	2 2	1 6	
	横方向 (A)		縦方向 (B)	3 . 0	4 6	4 2	3 8	3 5	4 3	3 9	3 5	3 2	3 6	3 3	3 1	2 8	3 1	2 8	2 6	2 4	1 7	
H m	1 . 5 9 H m	2 . 3 1 H m	4 . 0	4 8	4 4	4 1	3 8	4 5	4 1	3 8	3 6	3 8	3 6	3 3	3 1	3 2	3 0	2 8	2 7	2 0		
			5 . 0	4 9	4 6	4 3	4 1	4 6	4 3	4 1	3 8	4 0	3 7	3 5	3 3	3 4	3 2	3 0	2 9	2 1		
			7 . 0	5 1	4 8	4 6	4 4	4 8	4 5	4 3	4 1	4 1	3 9	3 8	3 6	3 5	3 4	3 2	3 1	2 4		
			1 0 . 0	5 2	5 0	4 9	4 7	4 9	4 7	4 6	4 4	4 3	4 1	4 0	3 9	3 6	3 5	3 4	3 3	2 5		

