

屋内照明器具特性	
品番 (品名)	L G W8 5 0 4 4 W F
光源	L D A 4 L - H - E 1 7 / S / 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 2 5 2 3 3 (1) D B 1
B Z 分類	B Z 4 / 0 . 7 / B Z 5

器具効率		7 7 %		反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
					壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
					床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
					室指数	照明率 (X 0 . 0 1) Z C M																
保守率		良 中 否	0 . 6 3	0 . 6	4 5	3 6	3 0	2 6	4 3	3 5	3 0	2 6	4 1	3 4	2 9	2 5	3 8	3 2	2 8	2 5	2 3	
			0 . 6	0 . 8	5 1	4 2	3 6	3 2	4 9	4 1	3 6	3 1	4 6	3 9	3 4	3 1	4 3	3 7	3 3	3 0	2 7	
			0 . 5 6	1 . 0	5 5	4 7	4 1	3 6	5 3	4 6	4 0	3 6	5 0	4 3	3 9	3 5	4 7	4 1	3 7	3 4	3 1	
				1 . 2 5	5 9	5 2	4 6	4 1	5 7	5 0	4 5	4 1	5 4	4 8	4 3	3 9	5 0	4 5	4 1	3 8	3 5	
下方投影面積		c m ²		1 . 5	6 2	5 5	5 0	4 5	6 0	5 4	4 9	4 5	5 6	5 1	4 7	4 3	5 3	4 8	4 5	4 2	3 8	
			等価発光面積	c m ²	2 . 0	6 6	6 0	5 5	5 1	6 4	5 9	5 4	5 0	6 0	5 6	5 2	4 8	5 7	5 3	5 0	4 7	4 3
取付 高さ	器具間隔最大限			2 . 5	6 9	6 4	5 9	5 5	6 7	6 2	5 8	5 4	6 3	5 9	5 5	5 2	5 9	5 6	5 3	5 0	4 6	
	横方向 (A)		縦方向 (B)		3 . 0	7 1	6 6	6 2	5 8	6 9	6 4	6 1	5 7	6 5	6 1	5 8	5 5	6 1	5 8	5 5	5 3	4 9
H m	1 . 1 4 H m		1 . 1 6 H m		4 . 0	7 3	6 9	6 6	6 3	7 1	6 8	6 4	6 2	6 7	6 4	6 1	5 9	6 3	6 1	5 9	5 7	5 3
					5 . 0	7 5	7 1	6 8	6 6	7 3	7 0	6 7	6 4	6 9	6 6	6 4	6 2	6 5	6 3	6 1	5 9	5 5
					7 . 0	7 6	7 4	7 2	6 9	7 4	7 2	7 0	6 8	7 0	6 9	6 7	6 5	6 7	6 5	6 4	6 2	5 8
					1 0 . 0	7 8	7 6	7 4	7 3	7 6	7 4	7 3	7 1	7 2	7 1	6 9	6 8	6 8	6 7	6 6	6 5	6 0

