

屋内照明器具特性	
品番 (品名)	L G W8 5 0 8 6 F
光源	LDA4 L - H - E17 / S / 4 ×1 440.0 lm
管理番号	K0172661 (0) DR 1
B Z 分類	BZ8

器具効率		63 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束		24 %	室指数	照明率 (X0.01)																	Z	CM
下方光束		39 %																				
保守率		良 中 否	0.63	0.6	29	20	15	12	26	19	14	11	23	17	13	10	19	14	11	8	6	
			0.6	0.8	34	26	21	17	31	24	19	16	27	21	17	14	23	18	15	12	8	
				1.0	38	30	24	20	35	28	23	19	30	24	20	17	25	21	17	15	11	
			0.56	1.25	41	34	29	24	38	32	27	23	33	28	24	20	28	24	20	18	13	
下方投影面積		cm ²		1.5	44	37	32	28	41	35	30	26	35	30	26	23	30	26	23	20	15	
等価発光面積			cm ²	2.0	47	41	37	33	44	39	34	31	38	34	30	27	32	29	26	24	18	
取付 高さ	器具間隔最大限			2.5	50	44	40	36	46	42	38	34	40	36	33	30	34	31	29	27	20	
	横方向 (A)		縦方向 (B)	3.0	51	47	43	39	48	44	40	37	42	38	35	33	36	33	31	29	22	
H m	1.49 H m		1.57 H m	4.0	54	50	46	43	50	47	44	41	44	41	38	36	38	36	34	32	25	
				5.0	55	52	49	46	52	49	46	43	45	43	41	39	39	37	35	34	26	
				7.0	57	54	52	49	53	51	49	47	47	45	43	42	41	39	38	37	29	
				10.0	58	56	54	52	55	53	51	50	48	47	46	44	42	41	40	39	31	

