

屋内照明器具特性	
品番 (品名)	LRD1032N
光源	LED5000_70_223 ×1 223.0 1m
管理番号	K0161907(1)DB1
BZ分類	BZ1

器具効率	100%	天井	80%				70%				50%				30%				0%	
			70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	反射率	壁	10%				10%				10%				10%				0%
下方光束	100%		床	10%				10%				10%				10%				0%
		室指数	照明率 (X0.01)																ZCM	
保守率	良	0.67	0.6	96	93	91	89	96	93	91	89	95	92	90	89	94	92	90	89	88
	中	0.63	0.8	99	96	94	92	98	96	94	92	97	95	93	92	96	94	93	92	91
	否	0.56	1.0	101	98	96	95	100	98	96	94	99	97	95	94	98	96	95	94	93
下方投影面積 等価発光面積	cm ²	cm ²	1.25	102	100	98	97	101	99	98	96	100	98	97	96	99	97	96	95	94
			1.5	103	101	99	98	102	100	99	98	101	99	98	97	100	98	97	96	95
			2.0	104	103	101	100	104	102	101	99	102	101	99	99	100	99	98	98	96
取付高さ	器具間隔最大限		2.5	105	104	102	101	104	103	102	101	102	101	100	101	100	101	100	99	97
	横方向 (A)	縦方向 (B)	3.0	106	104	103	102	105	103	102	101	103	102	101	100	101	100	100	99	97
Hm	0.37Hm	0.37Hm	4.0	106	105	104	103	105	104	103	103	103	103	102	101	102	101	100	98	
			5.0	107	106	105	104	106	105	104	103	104	103	103	102	102	101	101	100	98
			7.0	107	106	106	105	106	106	105	104	104	104	103	103	102	102	101	101	99
			10.0	108	107	107	106	106	106	106	105	104	104	104	103	102	102	102	102	99

