

屋内照明器具特性	
品番 (品名)	L G W8 5 1 1 6 W
光源	LDA4 L - H - E17 / S / 4 ×1 440.0 lm
管理番号	K0125722 (1) DB 1
B Z 分類	BZ5

器具効率		42 % 上方光束 5 % 下方光束 37 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
			室指数	照明率 (X0.01)																Z CM	
保守率		良 中 否	0.63	0.6	23	17	14	12	22	17	14	11	20	16	13	11	19	15	13	11	10
			0.6	0.8	27	22	18	16	26	21	18	15	24	20	17	15	22	19	16	14	13
			0.56	1.0	29	25	21	19	28	24	21	18	26	23	20	18	24	21	19	17	16
				1.25	32	27	24	22	31	27	24	21	28	25	23	21	27	24	22	20	18
下方投影面積		cm ²		1.5	33	30	26	24	32	29	26	24	30	27	25	23	28	26	24	22	20
等価発光面積			cm ²	2.0	36	33	30	28	35	32	29	27	32	30	28	26	30	28	26	25	23
				2.5	37	34	32	30	36	34	31	29	34	32	30	28	32	30	28	27	25
取付高さ	器具間隔最大限		3.0	38	36	34	32	37	35	33	31	35	33	31	30	33	31	30	28	26	
	横方向 (A)	縦方向 (B)																			
H m	1.24 H m	1.30 H m	4.0	40	38	36	34	39	37	35	34	36	35	33	32	34	33	32	31	28	
			5.0	41	39	37	36	39	38	36	35	37	36	35	34	35	34	33	32	30	
			7.0	42	40	39	38	40	39	38	37	38	37	36	35	36	35	34	34	31	
			10.0	42	41	41	40	41	40	40	39	39	38	38	37	37	36	36	35	32	

