

屋内照明器具特性	
品番 (品名)	L G W8 5 2 1 8 F
光源	LDA4 L - H - E17 / S / 4 ×1 440.0 lm
管理番号	K0168589 (0) DB 1
B Z 分類	BZ7 / 0.7 / BZ8 / 4.5 / BZ7

器具効率		5 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束 下方光束		1 3 % 4 1 %	室指数	照明率 (X 0 . 0 1) Z C M																				
保守率		良 中 否	0 . 6 3	0 . 6	0 . 6	0 . 5 6	0 . 6	2 6	1 9	1 5	1 2	2 5	1 8	1 4	1 1	2 2	1 7	1 3	1 0	2 0	1 5	1 2	1 0	8
			0 . 6	0 . 8	3 0	2 3	1 8	1 5	2 8	2 2	1 7	1 4	2 5	2 0	1 6	1 3	2 2	1 8	1 4	1 2	9			
			1 . 0	3 3	2 6	2 1	1 7	3 1	2 5	2 0	1 7	2 8	2 2	1 8	1 5	2 4	2 0	1 7	1 4	1 1				
			1 . 2 5	3 6	2 9	2 4	2 0	3 4	2 8	2 3	2 0	3 0	2 5	2 1	1 8	2 6	2 2	1 9	1 6	1 3				
下方投影面積		c m ²	1 . 5	3 8	3 2	2 7	2 3	3 6	3 0	2 6	2 2	3 2	2 7	2 4	2 0	2 8	2 4	2 1	1 9	1 5				
等価発光面積			c m ²	2 . 0	4 1	3 6	3 1	2 8	3 9	3 4	3 0	2 7	3 5	3 1	2 7	2 4	3 1	2 8	2 5	2 2	1 8			
取付高さ				器具間隔最大限			2 . 5	4 4	3 9	3 5	3 1	4 1	3 7	3 3	3 0	3 7	3 3	3 0	2 7	3 3	3 0	2 8	2 5	2 1
H m		0 . 6 5 H m	0 . 6 6 H m	3 . 0	4 5	4 1	3 7	3 4	4 3	3 9	3 6	3 2	3 9	3 5	3 2	3 0	3 5	3 2	3 0	2 7	2 3			
H m		0 . 6 5 H m	0 . 6 6 H m	4 . 0	4 7	4 4	4 1	3 8	4 5	4 2	3 9	3 6	4 1	3 8	3 6	3 3	3 7	3 5	3 3	3 1	2 6			
				5 . 0	4 9	4 6	4 3	4 0	4 7	4 4	4 1	3 9	4 2	4 0	3 8	3 6	3 8	3 6	3 5	3 3	2 8			
				7 . 0	5 1	4 8	4 6	4 4	4 8	4 6	4 4	4 2	4 4	4 2	4 1	3 9	4 0	3 9	3 7	3 6	3 1			
				1 0 . 0	5 2	5 0	4 8	4 7	5 0	4 8	4 7	4 5	4 6	4 4	4 3	4 2	4 2	4 0	3 9	3 8	3 3			

