

屋内照明器具特性	
品番 (品名)	L G W8 5 2 2 0 F
光源	L D A 4 L - H - E 1 7 / S / 4 × 1 4 4 0 . 0 l m
管理番号	K 0 1 8 9 6 7 3 (0) D B 1
B Z 分類	B Z 7

器具効率		4 8 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %		
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %		
上方光束 下方光束		8 % 4 0 %	室指数	照明率 (X 0 . 0 1) Z C M																			
保守率		良 中 否	0 . 6 3	0 . 6	0 . 5 6	0 . 6	2 3	1 7	1 3	1 0	2 2	1 6	1 2	1 0	2 0	1 5	1 2	9	1 8	1 4	1 1	9	7
			0 . 6	0 . 8	2 8	2 1	1 7	1 4	2 6	2 0	1 6	1 3	2 4	1 9	1 5	1 3	2 1	1 7	1 4	1 2	1 0		
			1 . 0	3 1	2 4	2 0	1 7	2 9	2 4	1 9	1 6	2 6	2 2	1 8	1 5	2 4	2 0	1 7	1 5	1 2			
			1 . 2 5	3 3	2 8	2 3	2 0	3 2	2 7	2 3	1 9	2 9	2 4	2 1	1 8	2 6	2 3	2 0	1 7	1 5			
下方投影面積		c m ²	1 . 5	3 5	3 0	2 6	2 3	3 4	2 9	2 5	2 2	3 1	2 7	2 3	2 1	2 8	2 5	2 2	1 9	1 7			
等価発光面積			c m ²	2 . 0	3 8	3 4	3 0	2 7	3 7	3 2	2 9	2 6	3 3	3 0	2 7	2 4	3 0	2 7	2 5	2 3	2 0		
取付 高さ	器具間隔最大限		2 . 5	4 0	3 6	3 2	2 9	3 8	3 5	3 1	2 9	3 5	3 2	2 9	2 7	3 2	3 0	2 7	2 5	2 2			
	横方向 (A) 縦方向 (B)		3 . 0	4 1	3 8	3 5	3 2	4 0	3 6	3 3	3 1	3 6	3 4	3 1	2 9	3 3	3 1	2 9	2 7	2 4			
H m	1 . 4 6 H m	1 . 4 5 H m	4 . 0	4 3	4 0	3 7	3 5	4 2	3 9	3 6	3 4	3 8	3 6	3 4	3 2	3 5	3 3	3 2	3 0	2 7			
			5 . 0	4 4	4 2	3 9	3 7	4 3	4 0	3 8	3 6	3 9	3 7	3 6	3 4	3 6	3 5	3 3	3 2	2 8			
			7 . 0	4 6	4 4	4 2	4 0	4 4	4 2	4 0	3 9	4 1	3 9	3 8	3 6	3 8	3 7	3 5	3 4	3 1			
			1 0 . 0	4 7	4 5	4 4	4 2	4 5	4 4	4 2	4 1	4 2	4 1	4 0	3 9	3 9	3 8	3 7	3 6	3 3			

